Zipline Eco

Continuous LED lighting system for industrial applications



Zipline Eco is designed for industrial applications, providing a faster and more flexible installation, combined with longevity and supreme efficiency (192.1 LL/CW).

The rolled steel trunking connects to a range of modules, which can be any combination of luminaire modules, emergency luminaire, or a passive infrared detector; they are designed to snap into the regularly spaced sockets on the trunking.

The Zipline Eco is a highly versatile industrial lighting system with five power options, broad, narrow, and double asymmetric light distributions and the SmartScan wireless lighting management system.

Applications: industrial, warehousing, and manufacturing.

- Narrow, broad or double asymmetric distribution luminaire module options
- Raw galvanised steel trunking
- Pre-installed wiring loom, module sockets at 1500 mm intervals
- Plug and socket connections between trunking joints
- Modules click fit using stainless steel spring (requires a standard screwdriver to release)
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit

Notes: See installation guide for mounting point locations

IP20 | Up to 190.1 LL/CW | SMARTSCAN | LUXGUARD

Specification

Mounting	**Surface** **Suspended**	IP rating	**IP20**
Nominal size	**1500 mm module**	Max presence detection height	**8 m**

Lighting

Distribution	**Broad** **Narrow**	Lumen output	**4,400 lm - 10,975 lm**
Efficacy	**Up to 190.1 LL/CW**		

Emergency data

Emergency lumen output	**675 lm - 690 lm**	Emergency type	**Maintained**
Emergency duration	**3 hours**	Battery specification	**Nickel Metal Hydride (NiMH)**

Power

LED power	**22 W - 64 W**	Circuit power	**24 W - 67 W**

Construction

Housing	**Zinc coated steel body**	Finish	**Full polyester powder coat**
Body colour	**Satin white (RAL9016)**	Optical assembly	**Polycarbonate high efficiency LED lenses**

LED characteristics


CRI	**80+**	Colour temperature	**4000 K**
Rated life (hours)	**100 K - L70/B10**	LED protection	**LUX Guard**
Driver efficiency	**>88%**	Replaceable light source	**Yes**
Power factor	**>0.9**	MacAdam ellipse	**3 Step**
Flicker metric	**IEC TR 61547-1: PstLM ≤1.0 / SVM ≤0.4**		

Compliance


UKCA	**Yes**	CE	**Yes**
Energy efficiency class	**This product contains a light source of energy efficiency class B**		

Dimensions

Suspension mounted version



End kit



Zipline Eco

Range

	Nominal size	LED power	Emergency system (optional)	Narrow	Broad	Double asymmetric	Lighting control system
SmartScan	1500 mm	22 W	**W**	**ZP16416**	**ZP16420**	**ZP16561**	**SS**
		33 W	**W**	**ZP16417**	**ZP16421**	**ZP16562**	**SS**
		41 W	**W**	**ZP16418**	**ZP16422**	**ZP16563**	**SS**
		53 W	**W**	**ZP16419**	**ZP16423**	**ZP16564**	**SS**
		64 W	**W**	**ZP16602**	**ZP16600**	**ZP16604**	**SS**
Standard	1500 mm	22 W	**E**	**ZP16424**	**ZP16428**	**ZP16565**	**A / L**
		33 W	**E**	**ZP16425**	**ZP16429**	**ZP16566**	**A / L**
		41 W	**E**	**ZP16426**	**ZP16430**	**ZP16567**	**A / L**
		53 W	**E**	**ZP16427**	**ZP16431**	**ZP16568**	**A / L**
		64 W	**E**	**ZP16603**	**ZP16601**	**ZP16605**	**A / L**

Emergency system - prefix catalogue number with **W** SmartScan Emergency / **E** Standard Emergency
Lighting control system - suffix catalogue number with **SS** SmartScan Internal / **A** Dimming (DALI) / **L** Non-dimming
E.g. **WZP16416SS** = 22 W / SmartScan Emergency / Narrow / SmartScan Internal

Additional Modules

Product code	Description	Weight
ZP16432	Presence detector - 750 mm module	0.9 kg
WZP19627	SmartScan Firefly Plus Emergency - Area downlighter - 750 mm module	1.3 kg
WZP19628	SmartScan Firefly Plus Emergency - Corridor downlighter - 750 mm module	1.3 kg
WZP16435	SmartScan Firefly Emergency - Area downlighter - 750 mm module	1.3 kg
WZP16436	SmartScan Firefly Emergency - Corridor downlighter - 750 mm module	1.3 kg

Trunking - Raw Galvanised Steel

Product code	Description	Weight
ZP20296	Raw galvanised steel trunking - 1.5 m straight - Pre-installed wiring loom, module sockets at 1500 mm intervals. Plug and socket connections between trunking joints.	2.6 kg
ZP20295	Raw galvanised steel trunking - 3.0 m straight - Pre-installed wiring loom, module sockets at 1500 mm intervals. Plug and socket connections between trunking joints.	5 kg
ZP20294	Raw galvanised steel trunking - 4.5 m straight - Pre-installed wiring loom, module sockets at 1500 mm intervals. Plug and socket connections between trunking joints.	7.2 kg

Finishing Components

Product code	Description	Weight
ZP16413	Trunking snap-in infill lid - Nominal 1.5 m lengths to be cut as required	0.3 kg
ZP20298	Raw galvanised steel trunking - End kit - One kit required per row. Includes live and dead end.	-
IK20299	Wire suspension kit - 3 m length - See mounting point spacing table in installation leaflet for required quantities	-
IK20491	Hoop wire suspension kit - 3 m length - See mounting point spacing table in installation leaflet for required quantities	0.04 kg
IK20494	Hoop wire suspension kit - 3 m length (10 pack) - See mounting point spacing table in installation leaflet for required quantities	0.45 kg

Zipline Eco





Click or scan here

View Zipline Eco variants using our online filtering tool



Information is correct as of 17-Nov-2026, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.