Cornisa

LED controller luminaires with asymmetric light distribution

Designed for cornice-mounting in a wide range of applications, the Cornisa is an LED controller luminaire with 45-degree asymmetric beam distribution.

Cornisa has been designed with BESA fixings located at 600 mm centres, with multiple cable entries to enable retrofitting without modifying the luminaire.

Applications: hospitals and healthcare buildings, schools, social housing, and residential.

- Assymetric beam distribution, ideal for cornice mounting
- Fire-retardant external plastic parts
- Designed to exclude dust, dirt and flies
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit.



IP40 | Up to 120 LL/CW | SMARTSCAN | LUXGUARD

Specification

Mounting	**Surface**	IP rating	**IP40**
Nominal size	**1500 mm**	Max presence detection height	**8 m**

Lighting

Optic	**Opal diffuser**	Distribution	**Asymmetric**
Lumen output	**3,000 lm - 5,755 lm**	Efficacy	**Up to 120 LL/CW**

Emergency data

Emergency lumen output	**340 lm**	Emergency type	**Maintained**
Emergency duration	**3 hours**	Battery specification	**Lithium Iron Phosphate (LiFePO4)**

Power

LED power	**22 W - 43 W**	Circuit power	**25 W - 49 W**

Cornisa

Construction

Housing	**Steel body and end caps**	Finish	**Full polyester powder coat**
Body colour	**Satin white (RAL9016)**	Optical assembly	**Polycarbonate diffuser**


LED characteristics

CRI	**80+**	Colour temperature	**4000 K**
Rated life (hours)	**100 K - L90/B10**	LED protection	**LUX Guard**
Driver efficiency	**>85%**	Replaceable light source	**Yes**
Power factor	**>0.9**	MacAdam ellipse	**3 Step**
Flicker metric	**IEC TR 61547-1: PstLM ≤1.0 / SVM ≤0.4**		

Compliance

UKCA	**Yes**	CE	**Yes**
Energy efficiency class	**This product contains a light source of energy efficiency class B**		

Dimensions



Range

Nominal size	LED power	Emergency system (optional)	CAT. No.	Lighting control system
1500 mm	22 W	**W*** / **T**** / **E****	**CN20236**	**SS / A / L**
	36 W	**W*** / **T**** / **E****	**CN20237**	**SS / A / L**
	43 W	**W*** / **T**** / **E****	**CN20238**	**SS / A / L**

* **Only** available with **SS** control type ** **Only** available with **A / L** control type

Emergency system - prefix catalogue number with **W** SmartScan Emergency / **T** AutoTest Emergency / **E** Standard Emergency
Lighting control system - suffix catalogue number with **SS** SmartScan Internal / **A** Dimming (DALI) / **L** Non-dimming

E.g. **WCN20236SS** = 1500 mm / 22 W / SmartScan Emergency / SmartScan Internal

Spares

Product code	Description	Weight
EMB650	Nickel Metal Hydride (NiMH) battery - End of life batteries can be returned to Thorlux for recycling	0.07 kg





Click or scan here

View Cornisa variants using our online filtering tool



Information is correct as of 17-Nov-2026, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.