

## IP65 sealed low depth LED canopy luminaires

PSL 65 has been designed for the illumination of petrol forecourts. With two mounting methods, wattages and light distributions, PSL 65 offers an effective solution for every forecourt.

SmartScan versions are available with a sensor optimised for mounting heights of up to 8 metres. This maintains excellent occupancy detection and removes the need for control cabling.

Application: petrol station forecourts.

- Recessed or surface mounting options
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



IP65

Up to 140.1 LL/CW

SMARTSCAN

LUXGUARD

### Specification

Mounting	Recessed Surface	IP rating	IP65
Max presence detection height	8 m		

### Lighting

Optic	Clear cover	Lumen output	7,045 lm - 8,785 lm
Efficacy	Up to 140.1 LL/CW		

### Power

LED power	46 W - 60 W	Circuit power	51 W - 66 W
-----------	-------------	---------------	-------------

### LED characteristics


CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L70/B10		

## Compliance

UKCA	Yes	CE	Yes
Energy efficiency class	This product contains a light source of energy efficiency class B		


## Dimensions

### Recessed



Minimum cut-out - 270 x 420  
Maximum cut-out - 600 x 600

### Surface



**Click or scan here**  
View PSL 65 variants using  
our online filtering tool



Information is correct as of 12-Feb-2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.