Starbeam Eco

LED floodlights and streetlights

Starbeam Eco is a supremely efficient, longer-life IP66 pole-top or wall-mounted LED floodlight luminaire with an aluminium cast body and fast-release gear compartment lid.

Designed to suit a range of external applications, Starbeam Eco's sealed acrylic lenses are available with either area or roadway light distributions. The luminaire includes an integral high-quality LED driver. Emergency, SmartScan, and photocell options are all available.

Applications: car parks, amenity areas, hospital estates, general roadway, and railway platforms.

- Strong high pressure die-cast LM6 aluminium body with acrylic high efficiency LED lenses
- Area or roadway optical distributions
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Wide range of mounting options, including wall mounting bracket
- Photocell option
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



Up to IP66 | IK08 | Up to 135.1 LL/CW | SMARTSCAN | LED PROTECT

Specification

Mounting	**Column** **Surface**	IP rating	**Up to IP66**
Impact rating	**IK08**	Max presence detection height	**8 m**

Lighting

Distribution	**Area** **Roadway**	Lumen output	**4,135 lm - 6,890 lm**
Efficacy	**Up to 135.1 LL/CW**	External upward light	**Zero upward light**

Emergency data

Emergency lumen output	**605 lm - 680 lm**	Emergency type	**Maintained**
Emergency duration	**3 hours**	Battery specification	**Nickel Metal Hydride (NiMH)**

Starbeam Eco

Power

LED power	**31 W - 48 W**	Circuit power	**35 W - 51 W**

Construction

Housing	**Die-cast aluminium body, lid and gear compartment**	Finish	**Full polyester powder coat**
Body colour	**Silver (RAL 9006) body / Graphite lid**	Optical assembly	**Acrylic high efficiency LED lenses**

LED characteristics

CRI	**70+**	Colour temperature	**4000 K**
Rated life (hours)	**100 K - L90/B10**	LED protection	**LED Protect**
Driver efficiency	**>90%**	Replaceable light source	**Yes**
Power factor	**>0.9**	MacAdam ellipse	**5 Step**
Flicker metric	**IEC TR 61547-1: PstLM ≤1.0 / SVM ≤0.4**		

Compliance

UKCA	**Yes**	CE	**Yes**
Energy efficiency class	**This product contains a light source of energy efficiency class C**		

Dimensions







Starbeam Eco

Range

	LED power	Emergency system (optional)	Area distribution	Roadway distribution	Lighting control system
SmartScan	31 W	**W**	**SB19673**	**SB19675**	**SS**
	48 W	**W**	**SB19674**	**SB19676**	**SS**
Standard	31 W	-	**SB19677**	**SB19679**	**L / LPC**
	48 W	-	**SB19678**	**SB19680**	**L / LPC**

Emergency system - prefix catalogue number with **W** SmartScan Emergency
Lighting control system - suffix catalogue number with **SS** SmartScan External / **L** Non-dimming / **LPC** Photocell (non-dimming)

E.g. **WSB19673SS** = 31 W / SmartScan Emergency / Area distribution / SmartScan External

Mounting Accessories

Product code	Description	Weight
SB15863	Single outreach arm - To fit on to 76 mm dia.	-
SB17788	Single outreach arm - To fit on to 89 mm dia.	-
SB15865	Single outreach arm - To fit on to 101 mm dia.	-
SB17180	Single outreach arm - To fit on to 114 mm dia.	-
SB15864	Twin outreach arm 180° - To fit on to 76 mm dia.	-
SB17789	Twin outreach arm 180° - To fit on to 89 mm dia.	-
SB15866	Twin outreach arm 180° - To fit on to 101mm dia.	-
SB17181	Twin outreach arm 180° - To fit on to 114 mm dia.	-
SB15890K	Twin outreach arm 90° - To fit on to 76 mm dia. - Supplied with 2 x 76-60 mm reducer kits (SB15809)	-
SB19695K	Twin outreach arm 90° - To fit on to 89 mm dia. - Supplied with 2 x 76-60 mm reducer kits (SB15809)	-
SB15893K	Twin outreach arm 90° - To fit on to 101 mm dia. - Supplied with 2 x 76-60 mm reducer kits (SB15809)	-
SB15896K	Triple outreach arm 120° - To fit on to 89 mm dia. - Supplied with 3 x 76-60 mm reducer kits (SB15809)	-
SB15894K	Triple outreach arm 120° - To fit on to 101 mm dia. - Supplied with 3 x 76-60 mm reducer kits (SB15809)	-
SB15897K	Quad outreach arm N-S-E-W - To fit on to 89 mm dia. - Supplied with 4 x 76-60 mm reducer kits (SB15809)	-
SB15895K	Quad outreach arm N-S-E-W - To fit on to 101 mm dia. - Supplied with 4 x 76-60 mm reducer kits (SB15809)	-
POT89-76	Column adaptor - 89-76 mm - To fit on to 89 mm dia.	-
POT101-76	Column adaptor - 101-76 mm - To fit on to 101 mm dia.	-
POT114-76	Column adaptor - 114-76 mm - To fit on to 114 mm dia.	-
SB15809	Bracket arm reducer - 76-60 mm - To fit on to 60 mm bracket arm	-
SB15810	Bracket arm reducer - 76-42 mm - To fit on to 42 mm bracket arm	-
SB15808	Wall mounting bracket	-

Single or Twin Luminaire Columns

Product code	Description	Weight
FC4	4 m - Standard duty column - 76 mm shaft diameter	33 kg
FC5	5 m - Standard duty column - 76 mm shaft diameter	40 kg
FC6	6 m - Standard duty column - 76 mm shaft diameter	44 kg
FC8	8 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	100 kg
FC10	10 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	142 kg

Triple or Quad Luminaire Columns

Product code	Description	Weight
FC4/89	4 m - Medium duty column - 89 mm shaft diameter	60 kg
FC5/89	5 m - Medium duty column - 89 mm shaft diameter	64 kg
FC6/89	6 m - Medium duty column - 89 mm shaft diameter	68 kg
FC8	8 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	100 kg
FC10	10 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	142 kg







Click or scan here

View Starbeam Eco variants using our online filtering tool



Information is correct as of 27 Nov 2026, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.