Starbeam Plus

LED area floodlights

IP66 wall- or pole-mounted LED luminaire with aluminium cast body and wiring box with glass cover. Integral high-quality driver. Emergency, SmartScan and photocell options.

Applications: car parks, amenity areas, sports areas, and large open spaces.

- Strong high pressure die-cast LM6 aluminium body with clear toughened/safety glass cover
- Area or flood distribution options
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Universal bracket for wall or column mounting
- Photocell option
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit

Notes: Warmer colour temperatures available to special order



Up to IP66 | **IK08** | **Up to 141.0 LL/CW** | SMARTSCAN | LED PROTECT

Specification

Mounting	**Column** **Surface**	IP rating	**Up to IP66**
Impact rating	**IK08**	Max presence detection height	**8 m**

Lighting

Optic	**Clear cover**	Distribution	**Area** **Flood**
Lumen output	**3,810 lm - 37,315 lm**	Efficacy	**Up to 141.0 LL/CW**
External upward light	**Zero upward light**		

Emergency data

Emergency type	**Maintained**	Emergency duration	**3 hours**
Battery specification	**Nickel Metal Hydride (NiMH)**		

Starbeam Plus

Power

LED power	**31 W - 276 W**	Circuit power	**35 W - 297 W**

Construction

Housing	**Strong high pressure die-cast LM6 aluminium body, lid and gear compartment**	Finish	**Full polyester powder coat**
Body colour	**Silver (RAL 9006)**	Optical assembly	**Toughened safety glass cover**

LED characteristics


CRI	**70+**	Colour temperature	**3000 K** **4000 K**
Rated life (hours)	**100 K - L90/B10**	LED protection	**LED Protect**
Driver efficiency	**>90%**	Replaceable light source	**Yes**
Power factor	**>0.9**	MacAdam ellipse	**5 Step**
Flicker metric	**IEC TR 61547-1: PstLM ≤1.0 / SVM ≤0.4**		

Compliance


UKCA	**Yes**	CE	**Yes**
Energy efficiency class	**This product contains a light source of energy efficiency class C**		

Dimensions

Large Version



Small Version



Starbeam Plus

Range

	Emergency system (optional)***	Product	LED power	Distribution	Colour temperature	Lighting control system
Small version	**W** SmartScan Emergency* **E** Standard Emergency**	**SM** Starbeam Plus	**031** 31 W **062** 62 W **088** 88 W **123** 123 W **161** 161 W	**A2** Area **A5** Flood	**3** 3000 K **4** 4000 K	**S** SmartScan External **L** Non-dimming **P** Photocell
Large version		**SM** Starbeam Plus	**197** 197 W **215** 215 W **276** 276 W	**A2** Area **A5** Flood	**3** 3000 K **4** 4000 K	**S** SmartScan External **L** Non-dimming **P** Photocell

* **Only** available with **S** control type ** **Only** available with **L / P** control type *** **Only** available on **31 W / 62 W / 88W** versions

E.g. **WSM031A23S** = Small version / SmartScan Emergency / Starbeam Plus / 31 W / Area distribution / 3000 K / SmartScan External

Mounting Accessories

Product code	Description	Weight
POT-89R	Single floodlight mounting pot - To fit on to 76 mm dia.	-
POT-101R	Single floodlight mounting pot - To fit on to 89 mm dia.	-
POT-114	Single floodlight mounting pot - To fit on to 101 mm dia.	-
POT-127	Single floodlight mounting pot - To fit on to 114 mm dia.	-
POT-140	Single floodlight mounting pot - To fit on to 127 mm dia.	-
CA2-89	Twin floodlight mounting crossarm - To fit on to 76 mm dia.	-
CA2-101	Twin floodlight mounting crossarm - To fit on to 89 mm dia.	-
CA2-114	Twin floodlight mounting crossarm - To fit on to 101 mm dia.	-
CA2-127	Twin floodlight mounting crossarm - To fit on to 114 mm dia.	-
CA2-140	Twin floodlight mounting crossarm - To fit on to 127 mm dia.	-
CA3-89	Triple floodlight mounting crossarm - To fit on to 76 mm dia.	-
CA3-101	Triple floodlight mounting crossarm - To fit on to 89 mm dia.	-
CA3-114	Triple floodlight mounting crossarm - To fit on to 101 mm dia.	-
CA3-127	Triple floodlight mounting crossarm - To fit on to 114 mm dia.	-
CA3-140	Triple floodlight mounting crossarm - To fit on to 127 mm dia.	-
CA4-89	Quad floodlight mounting crossarm - To fit on to 76 mm dia.	-
CA4-101	Quad floodlight mounting crossarm - To fit on to 89 mm dia.	-
CA4-114	Quad floodlight mounting crossarm - To fit on to 101 mm dia.	-
CA4-127	Quad floodlight mounting crossarm - To fit on to 114 mm dia.	-
CA4-140	Quad floodlight mounting crossarm - To fit on to 127 mm dia.	-

Single or Twin Luminaire Columns

Product code	Description	Weight
FC4	4 m - Standard duty column - 76 mm shaft diameter	33 kg
FC5	5 m - Standard duty column - 76 mm shaft diameter	40 kg
FC6	6 m - Standard duty column - 76 mm shaft diameter	44 kg
FC8	8 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	100 kg
FC10	10 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	142 kg

Triple or Quad Luminaire Columns

Product code	Description	Weight
FC4/89	4 m - Medium duty column - 89 mm shaft diameter	60 kg
FC5/89	5 m - Medium duty column - 89 mm shaft diameter	64 kg
FC6/89	6 m - Medium duty column - 89 mm shaft diameter	68 kg
FC8	8 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	100 kg
FC10	10 m - Medium duty column - 114 mm shaft diameter reduced at top to 101 mm	142 kg

Accessories

Product code	Description	Weight
SB20165	Rear shield - Small/large versions	0.4 kg
SB20162	Front shield - Small version	0.2 kg
SB20163	Side shield - Small version	0.2 kg
SB20328	Front shield - Large version	0.4 kg
SB20329	Side shield - Large version	0.4 kg





Click or scan here

View Starbeam Plus variants using our online filtering tool



Information is correct as of 27 Nov 2026, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.