

Press **CRTL + F** to search 

This document details the light efficacy performance for Thorlux luminaires in luminaire lumens per circuit watt (LL/CW). This is a measure of the total amount of light produced by the luminaire, which is then divided by the total power consumed. It is important that when making comparisons between luminaires from different manufacturers that the data presented is in the same format in order to make a fair judgement.

**NOTE** - All LED circuit wattage is based on fixed output control gear, apart from Smart versions which are based on dimmable DALI control gear. For other types of control gear please contact our Technical Department.

## Circuit Watts

The total power consumed in the lighting circuits by the lamps and their associated control gear.

## Luminaire Lumens

A measure of the total amount of light produced by the luminaire after all losses, such as optical losses, have been taken into account. This measure is the total amount of light being emitted into the space.

## LL/CW

Luminaire lumens per circuit watt is calculated by dividing the luminaire lumens with the circuit watts.

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
A-Line LED - Acrylic Cover - 41W	AL16516	46	6725	146.2
A-Line LED - Acrylic Cover - 58W	AL16517	66	9065	137.3
A-Line LED - Acrylic Cover SMART - 41W	AL17698	46	6725	146.2
A-Line LED - Acrylic Cover SMART - 58W	AL16515	66	9065	137.3
A-Line LED - Polycarbonate Cover - 29W - Ligature Resistant	AL16111	34	4270	125.6
A-Line LED - Polycarbonate Cover - 41W	AL16512	46	6335	137.7
A-Line LED - Polycarbonate Cover - 58W	AL16513	66	8540	129.4
A-Line LED - Polycarbonate Cover - 58W - Ligature Resistant	AL16110	66	8540	129.4
A-Line LED - Polycarbonate Cover SMART - 41W	AL17699	46	6335	137.7
A-Line LED - Polycarbonate Cover SMART - 58W	AL16511	66	8540	129.4
A-Line PRO - 101W - 1500mm - Acrylic - Broad Distribution	AP101LAB	114	18025	158.1
A-Line PRO - 101W - 1500mm - Acrylic - Narrow Distribution	AP101LAN	114	17645	154.8
A-Line PRO - 101W - 1500mm - Polycarbonate - Broad Distribution	AP101LPB	114	17455	153.1
A-Line PRO - 101W - 1500mm - Polycarbonate - Narrow Distribution	AP101LPN	114	17085	149.9
A-Line PRO - 16W - 1200mm - Acrylic - Broad Distribution	AP016MAB	21	3130	149.0
A-Line PRO - 16W - 1200mm - Acrylic - Narrow Distribution	AP016MAN	21	3065	146.0
A-Line PRO - 16W - 1200mm - Polycarbonate - Broad Distribution	AP016MPB	21	3030	144.3
A-Line PRO - 16W - 1200mm - Polycarbonate - Narrow Distribution	AP016MPN	21	2965	141.2
A-Line PRO - 20W - 1500mm - Acrylic - Broad Distribution	AP020LAB	25	4440	177.6
A-Line PRO - 20W - 1500mm - Acrylic - Narrow Distribution	AP020LAN	25	4345	173.8
A-Line PRO - 20W - 1500mm - Polycarbonate - Broad Distribution	AP020LPB	25	4300	172.0
A-Line PRO - 20W - 1500mm - Polycarbonate - Narrow Distribution	AP020LPN	25	4210	168.4
A-Line PRO - 26W - 1200mm - Acrylic - Broad Distribution	AP026MAB	32	5130	160.3
A-Line PRO - 26W - 1200mm - Acrylic - Narrow Distribution	AP026MAN	32	5020	156.9
A-Line PRO - 26W - 1200mm - Polycarbonate - Broad Distribution	AP026MPB	32	4970	155.3
A-Line PRO - 26W - 1200mm - Polycarbonate - Narrow Distribution	AP026MPN	32	4865	152.0
A-Line PRO - 32W - 1500mm - Acrylic - Broad Distribution	AP032LAB	42	7095	168.9
A-Line PRO - 32W - 1500mm - Acrylic - Narrow Distribution	AP032LAN	42	6945	165.4
A-Line PRO - 32W - 1500mm - Polycarbonate - Broad Distribution	AP032LPB	42	6870	163.6
A-Line PRO - 32W - 1500mm - Polycarbonate - Narrow Distribution	AP032LPN	42	6725	160.1
A-Line PRO - 41W - 1500mm - Acrylic - Broad Distribution	AP041LAB	49	8410	171.6
A-Line PRO - 41W - 1500mm - Acrylic - Narrow Distribution	AP041LAN	49	8235	168.1
A-Line PRO - 41W - 1500mm - Polycarbonate - Broad Distribution	AP041LPB	49	8145	166.2
A-Line PRO - 41W - 1500mm - Polycarbonate - Narrow Distribution	AP041LPN	49	7975	162.8
A-Line PRO - 44W - 1200mm - Acrylic - Broad Distribution	AP044MAB	55	8180	148.7
A-Line PRO - 44W - 1200mm - Acrylic - Narrow Distribution	AP044MAN	55	8010	145.6

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
A-Line PRO - 44W - 1200mm - Polycarbonate - Broad Distribution	AP044MPB	55	7920	144.0
A-Line PRO - 44W - 1200mm - Polycarbonate - Narrow Distribution	AP044MPN	55	7755	141.0
A-Line PRO - 56W - 1200mm - Acrylic - Broad Distribution	AP056MAB	71	11540	162.5
A-Line PRO - 56W - 1200mm - Acrylic - Narrow Distribution	AP056MAN	71	11295	159.1
A-Line PRO - 56W - 1200mm - Polycarbonate - Broad Distribution	AP056MPB	71	11175	157.4
A-Line PRO - 56W - 1200mm - Polycarbonate - Narrow Distribution	AP056MPN	71	10940	154.1
Arcadian - 21W 3000K	AN17074	25	2670	106.8
Arcadian - 21W 4000K	AN17075	25	2670	106.8
Arcadian - 27W 3000K	AN19208	32	3415	106.7
Arcadian - 27W 4000K	AN19209	32	3415	106.7
BLOX - MultiDrive (3) - 3x12W - Low Glare	BX3WSL04	42	3510	83.6
BLOX - MultiDrive (3) - 3x12W - Opal	BX3WSO04	42	4530	107.9
BLOX - MultiDrive (3) - 3x14W - Low Glare	BX3WSL04	48	3780	78.8
BLOX - MultiDrive (3) - 3x14W - Opal	BX3WSO04	48	4890	101.9
BLOX - MultiDrive (3) - 3x16W - Low Glare	BX3WSL04	57	4335	76.1
BLOX - MultiDrive (3) - 3x16W - Opal	BX3WSO04	60	5595	93.3
BLOX - MultiDrive (3) - 3x8W - Low Glare	BX3WSL04	30	2505	83.5
BLOX - MultiDrive (3) - 3x8W - Opal	BX3WSO04	30	3240	108.0
BLOX - MultiDrive (4) - 4x12W - Low Glare	BX4WSL04	56	4680	83.6
BLOX - MultiDrive (4) - 4x12W - Opal	BX4WSO04	56	6040	107.9
BLOX - MultiDrive (4) - 4x14W - Low Glare	BX4WSL04	64	5040	78.8
BLOX - MultiDrive (4) - 4x14W - Opal	BX4WSO04	64	6520	101.9
BLOX - MultiDrive (4) - 4x16W - Low Glare	BX4WSL04	57	5780	101.4
BLOX - MultiDrive (4) - 4x16W - Opal	BX4WSO04	76	7460	98.2
BLOX - MultiDrive (4) - 4x8W - Low Glare	BX4WSL04	40	3340	83.5
BLOX - MultiDrive (4) - 4x8W - Opal	BX4WSO04	40	4320	108.0
BLOX - Single Head - 16W - Low Glare	BX116L04	20	1170	58.5
BLOX - Single Head - 16W - Opal	BX116O04	20	1510	75.5
BLOX - Single Head - 8W - Low Glare	BX108L04	10	835	83.5
BLOX - Single Head - 8W - Opal	BX108O04	10	1080	108.0
Canolux LED - 116W - Recessed Mounted	CX14643	125	15100	120.8
Canolux LED - 116W - SMART - Recessed Mounted	CX14644	125	15100	120.8
Canolux LED - 116W - SMART - Surfaced Mounted	CX14642	125	15100	120.8
Canolux LED - 116W - Surfaced Mounted	CX14641	125	15100	120.8
Cirro LED Opal - 50W - 4000K	CRR19715	58	7315	126.1
Cirro LED Opal - 90W - 4000K	CRR19716	101	12540	124.2
Clara 180 - 20W	CA15854	23	2640	114.8
Clara 180 - 20W - SMART	CA19183	23	2640	114.8
Clara 180 uplight only - 10W	CA15853	13	1430	110.0
Clara 180 uplight only - 10W - SMART	CA19182	13	1430	110.0
Clara 360 - 20W	CA15625	24	2560	106.7
Clara 360 RGB - 20W	CA15628	24	2560	106.7
Clara 360 RGB SMART - 20W	CA15631	24	2560	106.7
Clara 360 SMART - 20W	CA15626	24	2560	106.7
Clara 360 White Halo - 20W	CA15634	24	2560	106.7
Clara 360 White Halo SMART - 20W	CA15637	24	2560	106.7
Clara 720 - 100W Opal Suspended	CA17393	116	13080	112.8
Clara 720 - 100W Opal Suspended - SMART	CA17391	116	13080	112.8
Clara 720 - 100W Satin Suspended	CA17286	116	14395	124.1
Clara 720 - 100W Satin Suspended - SMART	CA17284	116	14395	124.1
Clara 720 - 52W Opal Surface	CA17396	60	6705	111.8
Clara 720 - 52W Opal Surface - SMART	CA17394	60	6705	111.8
Clara 720 - 52W Satin Surface	CA17289	60	7290	121.5

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Clara 720 - 52W Satin Surface - SMART	CA17287	60	7290	121.5
Clara 720 - 59W Opal Suspended	CA17392	68	7790	114.6
Clara 720 - 59W Opal Suspended - SMART	CA17390	68	7790	114.6
Clara 720 - 59W Satin Suspended	CA17285	68	8235	121.1
Clara 720 - 59W Satin Suspended - SMART	CA17283	68	8235	121.1
Clara 720 - 80W Opal Surface	CA17397	92	10380	112.8
Clara 720 - 80W Opal Surface - SMART	CA17395	92	10380	112.8
Clara 720 - 80W Satin Surface	CA17290	92	11695	127.1
Clara 720 - 80W Satin Surface - SMART	CA17288	92	11695	127.1
Clara 90 - 10W	CA15851	13	755	58.1
Clara 90 - 20W	CA15852	24	1315	54.8
Cleanline LED LG7 Glass Cover - 26W - Ra80	CZ17996	30	2950	98.3
Cleanline LED LG7 Glass Cover - 26W - Ra90	CZ19030	30	2390	79.7
Cleanline LED LG7 Glass Cover - 38W - Ra80	CZ17997	44	4130	93.9
Cleanline LED LG7 Glass Cover - 38W - Ra90	CZ19031	44	3345	76.0
Cleanline LED LG7 Glass Cover SMART - 26W - Ra80	CZ17994	30	2950	98.3
Cleanline LED LG7 Glass Cover SMART - 26W - Ra90	CZ19024	30	2390	79.7
Cleanline LED LG7 Glass Cover SMART - 38W - Ra80	CZ17995	44	4130	93.9
Cleanline LED LG7 Glass Cover SMART - 38W - Ra90	CZ19025	44	3345	76.0
Cleanline LED LG7 Polycarbonate - 26W - Ra80	CZ18000	30	2905	96.8
Cleanline LED LG7 Polycarbonate - 26W - Ra90	CZ19032	30	2340	78.0
Cleanline LED LG7 Polycarbonate - 38W - Ra80	CZ18001	44	4080	92.7
Cleanline LED LG7 Polycarbonate - 38W - Ra90	CZ19033	44	3335	75.8
Cleanline LED LG7 Polycarbonate SMART - 26W - Ra80	CZ17998	30	2905	96.8
Cleanline LED LG7 Polycarbonate SMART - 26W - Ra90	CZ19026	30	2340	78.0
Cleanline LED LG7 Polycarbonate SMART - 38W - Ra80	CZ17999	44	4080	92.7
Cleanline LED LG7 Polycarbonate SMART - 38W - Ra90	CZ19027	44	3335	75.8
Cleanline LED Opal Polycarbonate - 26W - Ra80	CZ17002	30	3200	106.7
Cleanline LED Opal Polycarbonate - 26W - Ra90	CZ19034	30	2465	82.2
Cleanline LED Opal Polycarbonate - 38W - Ra80	CZ17003	44	4490	102.0
Cleanline LED Opal Polycarbonate - 38W - Ra90	CZ19035	44	3505	79.7
Cleanline LED Opal Polycarbonate SMART - 26W - Ra80	CZ17000	30	3200	106.7
Cleanline LED Opal Polycarbonate SMART - 26W - Ra90	CZ19028	30	2465	82.2
Cleanline LED Opal Polycarbonate SMART - 38W - Ra80	CZ17001	44	4490	102.0
Cleanline LED Opal Polycarbonate SMART - 38W - Ra90	CZ19029	44	3505	79.7
Cloud 10 - 63W - 4000K	CD19703	68	11015	162.0
Cloud 10 - 63W - SMART - 4000K	CD19703	68	11015	162.0
Cloud 4 - 29W - Colour Active	CD19700CA	35	4170	119.1
Cloud 4 - 29W - Colour Control	CD19700CC	35	4170	119.1
Cloud 4 - 30W - 4000K	CD19701	34	4170	122.6
Cloud 4 - 30W - SMART - 4000K	CD19701	34	4170	122.6
Cloud 7 - 54W - 4000K	CD19702	62	7520	121.3
Cloud 7 - 54W - SMART - 4000K	CD19702	62	7520	121.3
Cobalt LED Satin Hood - 15W - 4000K	CT19015	19	1020	53.7
Cobalt LED Satin Hood & Grill - 15W - 4000K	CT19016	19	855	45.0
Cobalt LED Satin Plain - 11W - 4000K	CT19516	14	1320	94.3
Cobalt LED Satin Plain - 16W - 4000K	CT19517	19	1795	94.5
Cobalt LED Satin Plain - 16W - 4000K - Ligature Resistant	CT16114	20	1810	90.5
Cobalt LED Satin Plain & Grill - 11W - 4000K	CT19518	14	1070	76.4
Cobalt LED Satin Plain & Grill - 16W - 4000K	CT19519	19	1455	76.6
Comboseal LED - 137W	CS18481	147	20070	136.5
Comboseal LED - 65W	CS18479	74	10255	138.6
Comboseal LED - 98W	CS18480	108	14970	138.6

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Comboseal LED SMART - 137W	CS18478	147	20070	136.5
Comboseal LED SMART - 65W	CS18476	74	10255	138.6
Comboseal LED SMART - 98W	CS18477	108	14970	138.6
Comboseal PLUS LED - 171W - Broad Distribution - High Ambient	CS18565	190	25490	134.2
Comboseal PLUS LED - 171W - Broad Distribution - Normal Ambient	CS18562	190	25490	134.2
Comboseal PLUS LED - 171W - Narrow Distribution - High Ambient	CS18571	190	25925	136.4
Comboseal PLUS LED - 171W - Narrow Distribution - Normal Ambient	CS18568	190	25925	136.4
Comboseal PLUS LED - 251W - Broad Distribution - High Ambient	CS18566	278	35505	127.7
Comboseal PLUS LED - 251W - Broad Distribution - Normal Ambient	CS18563	278	35505	127.7
Comboseal PLUS LED - 251W - Narrow Distribution - High Ambient	CS18572	278	36110	129.9
Comboseal PLUS LED - 251W - Narrow Distribution - Normal Ambient	CS18569	278	36110	129.9
Comboseal PLUS LED - 326W - Broad Distribution - High Ambient	CS18567	354	43725	123.5
Comboseal PLUS LED - 326W - Broad Distribution - Normal Ambient	CS18564	354	43725	123.5
Comboseal PLUS LED - 326W - Narrow Distribution - High Ambient	CS18573	354	44470	125.6
Comboseal PLUS LED - 326W - Narrow Distribution - Normal Ambient	CS18570	354	44470	125.6
Comboseal PLUS LED SMART - 171W - Broad Distribution - High Ambient	CS18553	190	25490	134.2
Comboseal PLUS LED SMART - 171W - Broad Distribution - Normal Ambient	CS18550	190	25490	134.2
Comboseal PLUS LED SMART - 171W - Narrow Distribution - High Ambient	CS18559	190	25925	136.4
Comboseal PLUS LED SMART - 171W - Narrow Distribution - Normal Ambient	CS18556	190	25925	136.4
Comboseal PLUS LED SMART - 251W - Broad Distribution - High Ambient	CS18554	278	35505	127.7
Comboseal PLUS LED SMART - 251W - Broad Distribution - Normal Ambient	CS18551	278	35505	127.7
Comboseal PLUS LED SMART - 251W - Narrow Distribution - High Ambient	CS18560	278	36110	129.9
Comboseal PLUS LED SMART - 251W - Narrow Distribution - Normal Ambient	CS18557	278	36110	129.9
Comboseal PLUS LED SMART - 326W - Broad Distribution - High Ambient	CS18555	354	43725	123.5
Comboseal PLUS LED SMART - 326W - Broad Distribution - Normal Ambient	CS18552	354	43725	123.5
Comboseal PLUS LED SMART - 326W - Narrow Distribution - High Ambient	CS18561	354	44470	125.6
Comboseal PLUS LED SMART - 326W - Narrow Distribution - Normal Ambient	CS18558	354	44470	125.6
Dot LED - Opal Cover - 13W	DOT17666	16	1865	116.6
Dot LED - Opal Cover - 14W	DOT16573	17	1380	81.2
Dot LED - Opal Cover - 17W	DOT16499	20	2465	123.3
Dot LED - Opal Cover SMART - 13W	DOT17657	16	1865	116.6
Dot LED - Opal Cover SMART - 14W	DOT16826	17	1380	81.2
Dot LED - Opal Cover SMART - 17W	DOT16493	20	2465	123.3
Dot LED - RGB Halo - Opal Cover - 13W	DOT17668	24	1865	77.7
Dot LED - RGB Halo - Opal Cover - 17W	DOT16501	29	2465	85.0
Dot LED - RGB Halo - Opal Cover SMART - 13W	DOT17659	23	1865	81.1
Dot LED - RGB Halo - Opal Cover SMART - 17W	DOT16495	27	2465	91.3
Dot LED - RGB Halo - Satin Cover - 13W	DOT17665	23	2500	108.7
Dot LED - RGB Halo - Satin Cover - 17W	DOT16498	27	3305	122.4
Dot LED - RGB Halo - Satin Cover SMART - 13W	DOT17656	23	2500	108.7
Dot LED - RGB Halo - Satin Cover SMART - 17W	DOT16492	27	3305	122.4
Dot LED - Satin Cover - 13W	DOT17663	16	2500	156.3
Dot LED - Satin Cover - 17W	DOT16496	20	3305	165.3
Dot LED - Satin Cover SMART - 13W	DOT17654	16	2500	156.3
Dot LED - Satin Cover SMART - 17W	DOT16490	20	3305	165.3
Dot LED - White Halo - Opal Cover - 13W	DOT17667	23	2470	107.4
Dot LED - White Halo - Opal Cover - 17W	DOT16500	27	3260	120.7
Dot LED - White Halo - Opal Cover SMART - 13W	DOT17658	23	2470	107.4
Dot LED - White Halo - Opal Cover SMART - 17W	DOT16494	27	3260	120.7
Dot LED - White Halo - Satin Cover - 13W	DOT17664	23	3100	134.8
Dot LED - White Halo - Satin Cover - 17W	DOT16497	27	4100	151.9
Dot LED - White Halo - Satin Cover SMART - 13W	DOT17655	23	3100	134.8
Dot LED - White Halo - Satin Cover SMART - 17W	DOT16491	27	4100	151.9

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
FGN-LED Type N (Zone 2 & 22) - 28W	FG16851	31	4310	139.0
FGN-LED Type N (Zone 2 & 22) - 42W	FG16852	46	5580	121.3
FGN-LED Type N (Zone 2 & 22) - 55W	FG16853	61	8540	140.0
FGN-Line Zone 2 & 22 - 1x58W	FG16960	55	5200	65.2
FGN-Line Zone 2 & 22 - 2x58W	FG16961	110	10400	55.8
Flexline corner - 1.8 - 21w - BLACK	FL1818CB	25	2180	87.2
Flexline corner - 1.8 - 21w - METALLISED	FL1818CM	25	3045	121.8
Flexline corner - 1.8 - 21w - WHITE	FL1818CW	25	2940	117.6
Flexline corner - 1.8 - 27w - BLACK	FL1818CB	31	2775	89.5
Flexline corner - 1.8 - 27w - METALLISED	FL1818CM	31	3880	125.2
Flexline corner - 1.8 - 27w - WHITE	FL1818CW	31	3740	120.6
Flexline corner - 1.8 - 32w - BLACK	FL1818CB	37	3260	88.1
Flexline corner - 1.8 - 32w - METALLISED	FL1818CM	37	4550	123.0
Flexline corner - 1.8 - 32w - WHITE	FL1818CW	37	4390	118.6
Flexline corner - 1.8 - 36w - BLACK	FL1818CB	41	3630	88.5
Flexline corner - 1.8 - 36w - METALLISED	FL1818CM	41	5070	123.7
Flexline corner - 1.8 - 36w - WHITE	FL1818CW	41	4890	119.3
Flexline corner - 2.4 - 28w - BLACK	FL2424CB	33	2910	88.2
Flexline corner - 2.4 - 28w - METALLISED	FL2424CM	33	4060	123.0
Flexline corner - 2.4 - 28w - WHITE	FL2424CW	33	3915	118.6
Flexline corner - 2.4 - 41w - BLACK	FL2424CB	48	4175	87.0
Flexline corner - 2.4 - 41w - METALLISED	FL2424CM	48	5830	121.5
Flexline corner - 2.4 - 41w - WHITE	FL2424CW	48	5625	117.2
Flexline corner - 2.4 - 48w - BLACK	FL2424CB	55	4840	88.0
Flexline corner - 2.4 - 48w - METALLISED	FL2424CM	55	6760	122.9
Flexline corner - 2.4 - 48w - WHITE	FL2424CW	55	6520	118.5
Flexline corner - 2.4 - 6w - BLACK	FL2424CB	42	3705	88.2
Flexline corner - 2.4 - 6w - METALLISED	FL2424CM	42	5170	123.1
Flexline corner - 2.4 - 6w - WHITE	FL2424CW	42	4990	118.8
Flexline rectangle - 2.4 x 1.2 - 29w - BLACK	FL2412QB	34	3010	88.5
Flexline rectangle - 2.4 x 1.2 - 29w - METALLISED	FL2412QM	34	4205	123.7
Flexline rectangle - 2.4 x 1.2 - 29w - WHITE	FL2412QW	34	4055	119.3
Flexline rectangle - 2.4 x 1.2 - 42w - BLACK	FL2412QB	49	4320	88.2
Flexline rectangle - 2.4 x 1.2 - 42w - METALLISED	FL2412QM	49	6035	123.2
Flexline rectangle - 2.4 x 1.2 - 42w - WHITE	FL2412QW	49	5820	118.8
Flexline rectangle - 2.4 x 1.2 - 54w - BLACK	FL2412QB	61	5500	90.2
Flexline rectangle - 2.4 x 1.2 - 54w - METALLISED	FL2412QM	61	7680	125.9
Flexline rectangle - 2.4 x 1.2 - 54w - WHITE	FL2412QW	61	7410	121.5
Flexline rectangle - 2.4 x 1.2 - 61w - BLACK	FL2412QB	69	6150	89.1
Flexline rectangle - 2.4 x 1.2 - 61w - METALLISED	FL2412QM	69	8590	124.5
Flexline rectangle - 2.4 x 1.2 - 61w - WHITE	FL2412QW	69	8285	120.1
Flexline single - 1.8 - 12w - BLACK	FL0018SB	16	1245	77.8
Flexline single - 1.8 - 12w - METALLISED	FL0018SM	16	1740	108.8
Flexline single - 1.8 - 12w - WHITE	FL0018SW	16	1680	105.0
Flexline single - 1.8 - 13w - BLACK	FL0018SB	17	1335	78.5
Flexline single - 1.8 - 13w - METALLISED	FL0018SM	17	1865	109.7
Flexline single - 1.8 - 13w - WHITE	FL0018SW	17	1800	105.9
Flexline single - 1.8 - 15w - BLACK	FL0018SB	19	1530	80.5
Flexline single - 1.8 - 15w - METALLISED	FL0018SM	19	2135	112.4
Flexline single - 1.8 - 15w - WHITE	FL0018SW	19	2060	108.4
Flexline single - 1.8 - 18w - BLACK	FL0018SB	22	1815	82.5
Flexline single - 1.8 - 18w - METALLISED	FL0018SM	22	2535	115.2
Flexline single - 1.8 - 18w - WHITE	FL0018SW	22	2445	111.1

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Flexline single - 2.4 - 14w - BLACK	FL0024SB	17	1455	85.6
Flexline single - 2.4 - 14w - METALLISED	FL0024SM	17	2030	119.4
Flexline single - 2.4 - 14w - WHITE	FL0024SW	17	1960	115.3
Flexline single - 2.4 - 18w - BLACK	FL0024SB	22	1850	84.1
Flexline single - 2.4 - 18w - METALLISED	FL0024SM	22	2585	117.5
Flexline single - 2.4 - 18w - WHITE	FL0024SW	22	2495	113.4
Flexline single - 2.4 - 21w - BLACK	FL0024SB	25	2140	85.6
Flexline single - 2.4 - 21w - METALLISED	FL0024SM	25	2985	119.4
Flexline single - 2.4 - 21w - WHITE	FL0024SW	25	2880	115.2
Flexline single - 2.4 - 24w - BLACK	FL0024SB	28	2420	86.4
Flexline single - 2.4 - 24w - METALLISED	FL0024SM	28	3380	120.7
Flexline single - 2.4 - 24w - WHITE	FL0024SW	28	3260	116.4
Flexline single - 3.6 - 21w - BLACK	FL0036SB	25	2180	87.2
Flexline single - 3.6 - 21w - METALLISED	FL0036SM	25	3045	121.8
Flexline single - 3.6 - 21w - WHITE	FL0036SW	25	2940	117.6
Flexline single - 3.6 - 27w - BLACK	FL0036SB	32	2775	86.7
Flexline single - 3.6 - 27w - METALLISED	FL0036SM	32	3880	121.3
Flexline single - 3.6 - 27w - WHITE	FL0036SW	32	3740	116.9
Flexline single - 3.6 - 32w - BLACK	FL0036SB	37	3260	88.1
Flexline single - 3.6 - 32w - METALLISED	FL0036SM	37	4550	123.0
Flexline single - 3.6 - 32w - WHITE	FL0036SW	37	4390	118.6
Flexline single - 3.6 - 36w - BLACK	FL0036SB	41	3630	88.5
Flexline single - 3.6 - 36w - METALLISED	FL0036SM	41	5070	123.7
Flexline single - 3.6 - 36w - WHITE	FL0036SW	41	4890	119.3
Flexline single - 4.8 - 28w - BLACK	FL0048SB	33	2910	88.2
Flexline single - 4.8 - 28w - METALLISED	FL0048SM	33	4060	123.0
Flexline single - 4.8 - 28w - WHITE	FL0048SW	33	3915	118.6
Flexline single - 4.8 - 36w - BLACK	FL0048SB	42	3705	88.2
Flexline single - 4.8 - 36w - METALLISED	FL0048SM	42	5170	123.1
Flexline single - 4.8 - 36w - WHITE	FL0048SW	42	4990	118.8
Flexline single - 4.8 - 42w - BLACK	FL0048SB	48	4275	89.1
Flexline single - 4.8 - 42w - METALLISED	FL0048SM	48	5975	124.5
Flexline single - 4.8 - 42w - WHITE	FL0048SW	48	5760	120.0
Flexline single - 4.8 - 49w - BLACK	FL0048SB	55	4940	89.8
Flexline single - 4.8 - 49w - METALLISED	FL0048SM	55	6900	125.5
Flexline single - 4.8 - 49w - WHITE	FL0048SW	55	6655	121.0
Flexline square - 1.8 - 29w - BLACK	FL1818QB	34	3010	88.5
Flexline square - 1.8 - 29w - METALLISED	FL1818QM	34	4205	123.7
Flexline square - 1.8 - 29w - WHITE	FL1818QW	34	4055	119.3
Flexline square - 1.8 - 42w - BLACK	FL1818QB	49	4320	88.2
Flexline square - 1.8 - 42w - METALLISED	FL1818QM	49	6035	123.2
Flexline square - 1.8 - 42w - WHITE	FL1818QW	49	5820	118.8
Flexline square - 1.8 - 54w - BLACK	FL1818QB	61	5500	90.2
Flexline square - 1.8 - 54w - METALLISED	FL1818QM	61	7680	125.9
Flexline square - 1.8 - 54w - WHITE	FL1818QW	61	7410	121.5
Flexline square - 1.8 - 61w - BLACK	FL1818QB	69	6150	89.1
Flexline square - 1.8 - 61w - METALLISED	FL1818QM	69	8590	124.5
Flexline square - 1.8 - 61w - WHITE	FL1818QW	69	8285	120.1
Flexline square - 2.4 - 39w - BLACK	FL2424QB	45	4050	90.0
Flexline square - 2.4 - 39w - METALLISED	FL2424QM	45	5655	125.7
Flexline square - 2.4 - 39w - WHITE	FL2424QW	45	5455	121.2
Flexline square - 2.4 - 56w - BLACK	FL2424QB	64	5760	90.0
Flexline square - 2.4 - 56w - METALLISED	FL2424QM	64	8045	125.7

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Flexline square - 2.4 - 56w - WHITE	FL2424QW	64	7760	121.3
Flexline square - 2.4 - 72w - BLACK	FL2424QB	79	7335	92.8
Flexline square - 2.4 - 72w - METALLISED	FL2424QM	79	10240	129.6
Flexline square - 2.4 - 72w - WHITE	FL2424QW	79	9880	125.1
Flexline square - 2.4 - 82w - BLACK	FL2424QB	90	8270	91.9
Flexline square - 2.4 - 82w - METALLISED	FL2424QM	90	11550	128.3
Flexline square - 2.4 - 82w - WHITE	FL2424QW	90	11140	123.8
Flexline twin - 1.8 - 14w - BLACK	FL0018TB	17	1455	85.6
Flexline twin - 1.8 - 14w - METALLISED	FL0018TM	17	2030	119.4
Flexline twin - 1.8 - 14w - WHITE	FL0018TW	17	1960	115.3
Flexline twin - 1.8 - 22w - BLACK	FL0018TB	25	2265	90.6
Flexline twin - 1.8 - 22w - METALLISED	FL0018TM	25	3160	126.4
Flexline twin - 1.8 - 22w - WHITE	FL0018TW	25	3050	122.0
Flexline twin - 1.8 - 27w - BLACK	FL0018TB	30	2750	91.7
Flexline twin - 1.8 - 27w - METALLISED	FL0018TM	30	3840	128.0
Flexline twin - 1.8 - 27w - WHITE	FL0018TW	30	3705	123.5
Flexline twin - 1.8 - 31w - BLACK	FL0018TB	34	3125	91.9
Flexline twin - 1.8 - 31w - METALLISED	FL0018TM	34	4365	128.4
Flexline twin - 1.8 - 31w - WHITE	FL0018TW	34	4210	123.8
Flexline twin - 2.4 - 19w - BLACK	FL0024TB	22	1975	89.8
Flexline twin - 2.4 - 19w - METALLISED	FL0024TM	22	2755	125.2
Flexline twin - 2.4 - 19w - WHITE	FL0024TW	22	2660	120.9
Flexline twin - 2.4 - 28w - BLACK	FL0024TB	31	2880	92.9
Flexline twin - 2.4 - 28w - METALLISED	FL0024TM	31	4020	129.7
Flexline twin - 2.4 - 28w - WHITE	FL0024TW	31	3880	125.2
Flexline twin - 2.4 - 36w - BLACK	FL0024TB	40	3665	91.6
Flexline twin - 2.4 - 36w - METALLISED	FL0024TM	40	5120	128.0
Flexline twin - 2.4 - 36w - WHITE	FL0024TW	40	4940	123.5
Flexline twin - 2.4 - 41w - BLACK	FL0024TB	45	4135	91.9
Flexline twin - 2.4 - 41w - METALLISED	FL0024TM	45	5775	128.3
Flexline twin - 2.4 - 41w - WHITE	FL0024TW	45	5570	123.8
Flexline twin - 3.6 - 28w - BLACK	FL0036TB	33	2910	88.2
Flexline twin - 3.6 - 28w - METALLISED	FL0036TM	33	4060	123.0
Flexline twin - 3.6 - 28w - WHITE	FL0036TW	33	3915	118.6
Flexline twin - 3.6 - 42w - BLACK	FL0036TB	49	4320	88.2
Flexline twin - 3.6 - 42w - METALLISED	FL0036TM	49	6035	123.2
Flexline twin - 3.6 - 42w - WHITE	FL0036TW	49	5820	118.8
Flexline twin - 3.6 - 54w - BLACK	FL0036TB	61	5500	90.2
Flexline twin - 3.6 - 54w - METALLISED	FL0036TM	61	7680	125.9
Flexline twin - 3.6 - 54w - WHITE	FL0036TW	61	7410	121.5
Flexline twin - 3.6 - 61w - BLACK	FL0036TB	69	6150	89.1
Flexline twin - 3.6 - 61w - METALLISED	FL0036TM	69	8590	124.5
Flexline twin - 3.6 - 61w - WHITE	FL0036TW	69	8285	120.1
Flexline twin - 4.8 - 39w - BLACK	FL0048TB	45	4050	90.0
Flexline twin - 4.8 - 39w - METALLISED	FL0048TM	45	5655	125.7
Flexline twin - 4.8 - 39w - WHITE	FL0048TW	45	5455	121.2
Flexline twin - 4.8 - 56w - BLACK	FL0048TB	64	5760	90.0
Flexline twin - 4.8 - 56w - METALLISED	FL0048TM	64	8045	125.7
Flexline twin - 4.8 - 56w - WHITE	FL0048TW	64	7760	121.3
Flexline twin - 4.8 - 72w - BLACK	FL0048TB	79	7335	92.8
Flexline twin - 4.8 - 72w - METALLISED	FL0048TM	79	10240	129.6
Flexline twin - 4.8 - 72w - WHITE	FL0048TW	79	9880	125.1
Flexline twin - 4.8 - 82w - BLACK	FL0048TB	90	8270	91.9



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Flexline twin - 4.8 - 82w - METALLISED	FL0048TM	90	11550	128.3
Flexline twin - 4.8 - 82w - WHITE	FL0048TW	90	11140	123.8
Flexview eight - 67w - BLACK	FV1224SB	77	3820	49.6
Flexview eight - 67w - METALLISED	FV1224SM	77	4685	60.8
Flexview eight - 67w - WHITE	FV1224SW	77	4580	59.5
Flexview eight - 74w - BLACK	FV1224SB	84	4520	53.8
Flexview eight - 74w - METALLISED	FV1224SM	84	5660	67.4
Flexview eight - 74w - WHITE	FV1224SW	84	5520	65.7
Flexview eight - 82w - BLACK	FV1224SB	92	5305	57.7
Flexview eight - 82w - METALLISED	FV1224SM	92	6760	73.5
Flexview eight - 82w - WHITE	FV1224SW	92	6580	71.5
Flexview eight - 87w - BLACK	FV1224SB	97	5775	59.5
Flexview eight - 87w - METALLISED	FV1224SM	97	7415	76.4
Flexview eight - 87w - WHITE	FV1224SW	97	7210	74.3
Flexview four - 37w - BLACK	FV1212SB	46	2275	49.5
Flexview four - 37w - METALLISED	FV1212SM	46	2850	62.0
Flexview four - 37w - WHITE	FV1212SW	46	2780	60.4
Flexview four - 41w - BLACK	FV1212SB	50	2670	53.4
Flexview four - 41w - METALLISED	FV1212SM	50	3405	68.1
Flexview four - 41w - WHITE	FV1212SW	50	3315	66.3
Flexview four - 47w - BLACK	FV1212SB	56	3265	58.3
Flexview four - 47w - METALLISED	FV1212SM	56	4235	75.6
Flexview four - 47w - WHITE	FV1212SW	56	4115	73.5
Flexview four - 50w - BLACK	FV1212SB	59	3545	60.1
Flexview four - 50w - METALLISED	FV1212SM	59	4625	78.4
Flexview four - 50w - WHITE	FV1212SW	59	4490	76.1
Flexview one - 20w - BLACK	FV0606SB	24	1630	67.9
Flexview one - 20w - METALLISED	FV0606SM	24	2195	91.5
Flexview one - 20w - WHITE	FV0606SW	24	2125	88.5
Flexview one - 26w - BLACK	FV0606SB	30	2200	73.3
Flexview one - 26w - METALLISED	FV0606SM	30	2995	99.8
Flexview one - 26w - WHITE	FV0606SW	30	2895	96.5
Flexview one - 34w - BLACK	FV0606SB	39	2945	75.5
Flexview one - 34w - METALLISED	FV0606SM	39	4030	103.3
Flexview one - 34w - WHITE	FV0606SW	39	3895	99.9
Flexview one - 40w - BLACK	FV0606SB	45	3460	76.9
Flexview one - 40w - METALLISED	FV0606SM	45	4755	105.7
Flexview one - 40w - WHITE	FV0606SW	45	4590	102.0
Flexview six - 52w - BLACK	FV1812SB	59	2995	50.8
Flexview six - 52w - METALLISED	FV1812SM	59	3695	62.6
Flexview six - 52w - WHITE	FV1812SW	59	3610	61.2
Flexview six - 58w - BLACK	FV1812SB	65	3595	55.3
Flexview six - 58w - METALLISED	FV1812SM	65	4535	69.8
Flexview six - 58w - WHITE	FV1812SW	65	4415	67.9
Flexview six - 65w - BLACK	FV1812SB	73	4285	58.7
Flexview six - 65w - METALLISED	FV1812SM	73	5495	75.3
Flexview six - 65w - WHITE	FV1812SW	73	5345	73.2
Flexview six - 69w - BLACK	FV1812SB	77	4660	60.5
Flexview six - 69w - METALLISED	FV1812SM	77	6020	78.2
Flexview six - 69w - WHITE	FV1812SW	77	5850	76.0
Flexview sixteen - 121w - BLACK	FV2424SB	135	6190	45.9
Flexview sixteen - 121w - METALLISED	FV2424SM	135	7340	54.4
Flexview sixteen - 121w - WHITE	FV2424SW	135	7195	53.3



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Flexview sixteen - 130w - BLACK	FV2424SB	145	7085	48.9
Flexview sixteen - 130w - METALLISED	FV2424SM	145	8595	59.3
Flexview sixteen - 130w - WHITE	FV2424SW	145	8405	58.0
Flexview sixteen - 141w - BLACK	FV2424SB	157	8170	52.0
Flexview sixteen - 141w - METALLISED	FV2424SM	157	10110	64.4
Flexview sixteen - 141w - WHITE	FV2424SW	157	9865	62.8
Flexview sixteen - 148w - BLACK	FV2424SB	164	8825	53.8
Flexview sixteen - 148w - METALLISED	FV2424SM	164	11025	67.2
Flexview sixteen - 148w - WHITE	FV2424SW	164	10750	65.5
Flute LED Aluminium Reflector - 24W	SH15158	27	1835	68.0
Flute LED Aluminium Reflector - 36W	SH15159	39	2640	67.7
Flute LED Polycarbonate Refractor- 24W	SH15156	27	2845	105.4
Flute LED Polycarbonate Refractor- 36W	SH15157	39	4095	105.0
Folio 4m single - 50W 4000K	FL17533	54	4275	79.2
Folio 4m single - 50W 5700K	FL16161	54	4275	79.2
Folio 4m single SMART - 50W 4000K	FL17528	54	4275	79.2
Folio 4m single SMART - 50W 5700K	FL16160	54	4275	79.2
Folio 6m single - 50W 4000K	FL17534	54	4275	79.2
Folio 6m single - 50W 5700K	FL16163	54	4275	79.2
Folio 6m single SMART - 50W 4000K	FL17529	54	4275	79.2
Folio 6m single SMART - 50W 5700K	FL16162	54	4275	79.2
Folio wall mounted - 50W 4000K	FL17537	54	4275	79.2
Folio wall mounted - 50W 5700K	FL16169	54	4275	79.2
Folio wall mounted SMART - 50W 4000K	FL17532	54	4275	79.2
Folio wall mounted SMART - 50W 5700K	FL16168	54	4275	79.2
G1 MRI LED - 15W - 4000K	GM19048	18	1880	104.4
G2 LED Blue Poly Halo - 12W	GU15407 + GU13677	15	925	61.7
G2 LED Blue Poly Halo - 6W	GU15406 + GU13677	8	465	58.1
G2 LED Clear Cone - 12W	GU15407 + GU13675	15	1000	66.7
G2 LED Clear Cone - 6W	GU15406 + GU13675	8	505	63.1
G2 LED Clear Poly Halo - 12W	GU15407 + GU13676	15	1125	75.0
G2 LED Clear Poly Halo - 6W	GU15406 + GU13676	8	570	71.3
G2 LED Drop Glass - 12W	GU15407 + GU14177W	15	1040	69.3
G2 LED Drop Glass - 6W	GU15406 + GU14177W	8	525	65.6
G2 LED Frosted Sealed Glass - 12W	GU15407 + GU13679G	15	860	57.3
G2 LED Frosted Sealed Glass - 6W	GU15406 + GU13679G	8	435	54.4
G2 LED Poly Prismatic Lens - 12W	GU15407 + GU13681	15	650	43.3
G2 LED Poly Prismatic Lens - 6W	GU15406 + GU13681	8	325	40.6
G2 LED Poly Prismatic Sided Dish - 12W	GU15407 + GU13682	15	1000	66.7
G2 LED Poly Prismatic Sided Dish - 6W	GU15406 + GU13682	8	505	63.1
G2 LED White Bezel - 12W	GU15407 + GU14176W	15	1190	79.3
G2 LED White Bezel - 6W	GU15406 + GU14176W	8	600	75.0
G2 Pismatic Polycarbonate - 12W - Ligature-Resistant - 4000K	GU16837	15	650	43.3
G2 Prismatic Polycarbonate - 6W - Ligature-Resistant - 4000K	GU16835	8	325	40.6
G2 Satin Polycarbonate - 12W - Ligature-Resistant - 4000K	GU16836	15	670	44.7
G2 Satin Polycarbonate - 6W - Ligature-Resistant - 4000K	GU16834	8	340	42.5
G3 LED - 12W - ColourControl	GT18824CC	15	965	64.3
G3 LED - 12W - SMART - ColourActive	GT18822CA	15	965	64.3
G3 LED - 24W - ColourControl	GT18825CC	30	2050	68.3
G3 LED - 24W - SMART - ColourActive	GT18823CA	30	2050	68.3
G3 LED Frosted Inner Drop Glass - 16W - 3000K	GT18398	20	1715	85.8
G3 LED Frosted Inner Drop Glass - 16W - 4000K	GT15077	20	1825	91.3
G3 LED Frosted Inner Drop Glass - 21W - 3000K	GT18399	26	2165	83.3

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
G3 LED Frosted Inner Drop Glass - 21W - 4000K	GT18375	26	2305	88.7
G3 LED Frosted Inner Drop Glass - 8W - 3000K	GT18379	10	940	94.0
G3 LED Frosted Inner Drop Glass - 8W - 4000K	GT15076	10	1000	100.0
G3 LED Frosted Inner Drop Glass SMART - 16W - 3000K	GT18395	20	1715	85.8
G3 LED Frosted Inner Drop Glass SMART - 16W - 4000K	GT15078	20	1825	91.3
G3 LED Frosted Inner Drop Glass SMART - 21W - 3000K	GT18396	26	2165	83.3
G3 LED Frosted Inner Drop Glass SMART - 21W - 4000K	GT18374	26	2305	88.7
G3 LED Frosted Outer Drop Glass - 16W - 3000K	GT18393	20	1790	89.5
G3 LED Frosted Outer Drop Glass - 16W - 4000K	GT15074	20	1905	95.3
G3 LED Frosted Outer Drop Glass - 21W - 3000K	GT18394	26	2260	86.9
G3 LED Frosted Outer Drop Glass - 21W - 4000K	GT18373	26	2410	92.7
G3 LED Frosted Outer Drop Glass - 8W - 3000K	GT18392	10	985	98.5
G3 LED Frosted Outer Drop Glass - 8W - 4000K	GT15073	10	1050	105.0
G3 LED Frosted Outer Drop Glass SMART - 16W - 3000K	GT18390	20	1790	89.5
G3 LED Frosted Outer Drop Glass SMART - 16W - 4000K	GT15075	20	1905	95.3
G3 LED Frosted Outer Drop Glass SMART - 21W - 3000K	GT18391	26	2260	86.9
G3 LED Frosted Outer Drop Glass SMART - 21W - 4000K	GT18372	26	2410	92.7
G3 LED Halo - 16W - 3000K	GT18403	20	1985	99.3
G3 LED Halo - 16W - 4000K	GT15080	20	2115	105.8
G3 LED Halo - 21W - 3000K	GT18404	26	2505	96.3
G3 LED Halo - 21W - 4000K	GT18377	26	2670	102.7
G3 LED Halo - 8W - 3000K	GT18402	10	1095	109.5
G3 LED Halo - 8W - 4000K	GT15079	10	1165	116.5
G3 LED Halo SMART - 16W - 3000K	GT18400	20	1985	99.3
G3 LED Halo SMART - 16W - 4000K	GT15081	20	2115	105.8
G3 LED Halo SMART - 21W - 3000K	GT18401	26	2505	96.3
G3 LED Halo SMART - 21W - 4000K	GT18376	26	2670	102.7
G3 LED IK10 Polycarbonate - 16W - 3000K	GT18406	20	1870	93.5
G3 LED IK10 Polycarbonate - 16W - 4000K	GT15083	20	1990	99.5
G3 LED IK10 Polycarbonate - 21W - 3000K	GT18407	26	2360	90.8
G3 LED IK10 Polycarbonate - 21W - 4000K	GT18378	26	2515	96.7
G3 LED IK10 Polycarbonate - 8W - 3000K	GT18405	10	1030	103.0
G3 LED IK10 Polycarbonate - 8W - 4000K	GT15082	10	1095	109.5
G3 LED IP65 Clear Glass - 16W - 3000K	GT18412	20	1910	95.5
G3 LED IP65 Clear Glass - 16W - 4000K	GT15086	20	2035	101.8
G3 LED IP65 Clear Glass - 21W - 3000K	GT18413	26	2410	92.7
G3 LED IP65 Clear Glass - 21W - 4000K	GT18382	26	2565	98.7
G3 LED IP65 Clear Glass - 8W - 3000K	GT18411	10	1050	105.0
G3 LED IP65 Clear Glass - 8W - 4000K	GT15085	10	1120	112.0
G3 LED IP65 Clear Polycarbonate - 16W - 3000K	GT18418	20	1820	91.0
G3 LED IP65 Clear Polycarbonate - 16W - 4000K	GT15092	20	1940	97.0
G3 LED IP65 Clear Polycarbonate - 16W - 4000K - Ligature Resistant	GT17231	20	1940	97.0
G3 LED IP65 Clear Polycarbonate - 21W - 3000K	GT18419	26	2300	88.5
G3 LED IP65 Clear Polycarbonate - 21W - 4000K	GT18384	26	2450	94.2
G3 LED IP65 Clear Polycarbonate - 8W - 3000K	GT18417	10	1000	100.0
G3 LED IP65 Clear Polycarbonate - 8W - 4000K	GT15091	10	1065	106.5
G3 LED IP65 Clear Polycarbonate - 8W - 4000K - Ligature Resistant	GT17230	10	1065	106.5
G3 LED IP65 Frosted Glass - 16W - 3000K	GT18415	20	1685	84.3
G3 LED IP65 Frosted Glass - 16W - 4000K	GT15089	20	1795	89.8
G3 LED IP65 Frosted Glass - 21W - 3000K	GT18416	26	2125	81.7
G3 LED IP65 Frosted Glass - 21W - 4000K	GT18383	26	2265	87.1
G3 LED IP65 Frosted Glass - 8W - 3000K	GT18414	10	925	92.5
G3 LED IP65 Frosted Glass - 8W - 4000K	GT15088	10	985	98.5

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
G3 LED IP65 Satin Polycarbonate - 16W - 4000K - Ligature Resistant	GT17233	20	1650	82.5
G3 LED IP65 Satin Polycarbonate - 8W - 4000K - Ligature Resistant	GT17232	10	835	83.5
G3 LED Open - 16W - 3000K	GT18388	20	2075	103.8
G3 LED Open - 16W - 4000K	GT15071	20	2210	110.5
G3 LED Open - 21W - 3000K	GT18389	26	2620	100.8
G3 LED Open - 21W - 4000K	GT18371	26	2790	107.3
G3 LED Open - 8W - 3000K	GT18387	10	1140	114.0
G3 LED Open - 8W - 4000K	GT15070	10	1215	121.5
G3 LED Open SMART 16W - 3000K	GT18385	20	2075	103.8
G3 LED Open SMART 16W - 4000K	GT15072	20	2210	110.5
G3 LED Open SMART 21W - 3000K	GT18386	26	2620	100.8
G3 LED Open SMART 21W - 4000K	GT18370	26	2790	107.3
G3 PRO LED Black Reflector - 11W - Broad Distribution - 3000K	GT19898	14	1570	112.1
G3 PRO LED Black Reflector - 11W - Broad Distribution - 3000K	GT19404	14	1570	112.1
G3 PRO LED Black Reflector - 11W - Broad Distribution - 4000K	GT19902	14	1670	119.3
G3 PRO LED Black Reflector - 11W - Broad Distribution - 4000K	GT19408	14	1690	120.7
G3 PRO LED Black Reflector - 11W - SMART - Broad Distribution - 3000K	GT19396	14	1570	112.1
G3 PRO LED Black Reflector - 11W - SMART - Broad Distribution - 4000K	GT19400	14	1690	120.7
G3 PRO LED Black Reflector - 24W - Broad Distribution - 3000K	GT19899	29	3010	103.8
G3 PRO LED Black Reflector - 24W - Broad Distribution - 3000K	GT19405	28	3010	107.5
G3 PRO LED Black Reflector - 24W - Broad Distribution - 4000K	GT19903	29	3235	111.6
G3 PRO LED Black Reflector - 24W - Broad Distribution - 4000K	GT19409	28	3235	115.5
G3 PRO LED Black Reflector - 24W - SMART - Broad Distribution - 3000K	GT19397	28	3010	107.5
G3 PRO LED Black Reflector - 24W - SMART - Broad Distribution - 4000K	GT19401	28	3235	115.5
G3 PRO LED Black Reflector - 40W - Broad Distribution - 3000K	GT19900	45	4485	99.7
G3 PRO LED Black Reflector - 40W - Broad Distribution - 4000K	GT19904	45	4820	107.1
G3 PRO LED Black Reflector - 40W - Narrow Distribution - 3000K	GT19901	45	4420	98.2
G3 PRO LED Black Reflector - 40W - Narrow Distribution - 4000K	GT19905	45	4755	105.7
G3 PRO LED Black Reflector - 51W - Broad Distribution - 3000K	GT19406	57	5255	92.2
G3 PRO LED Black Reflector - 51W - Broad Distribution - 4000K	GT19410	57	5650	99.1
G3 PRO LED Black Reflector - 51W - Narrow Distribution - 3000K	GT19407	57	5415	95.0
G3 PRO LED Black Reflector - 51W - Narrow Distribution - 4000K	GT19411	57	5825	102.2
G3 PRO LED Black Reflector - 51W - SMART - Broad Distribution - 3000K	GT19389	57	5255	92.2
G3 PRO LED Black Reflector - 51W - SMART - Broad Distribution - 4000K	GT19402	57	5650	99.1
G3 PRO LED Black Reflector - 51W - SMART - Narrow Distribution - 3000K	GT19399	57	5415	95.0
G3 PRO LED Black Reflector - 51W - SMART - Narrow Distribution - 4000K	GT19403	57	5825	102.2
G3 PRO LED White Reflector - 11W - Broad Distribution - 3000K	GT19890	14	1580	112.9
G3 PRO LED White Reflector - 11W - Broad Distribution - 3000K	GT19388	14	1580	112.9
G3 PRO LED White Reflector - 11W - Broad Distribution - 4000K	GT19894	14	1700	121.4
G3 PRO LED White Reflector - 11W - Broad Distribution - 4000K	GT19392	14	1700	121.4
G3 PRO LED White Reflector - 11W - SMART - Broad Distribution - 3000K	GT19380	14	1580	112.9
G3 PRO LED White Reflector - 11W - SMART - Broad Distribution - 4000K	GT19384	14	1700	121.4
G3 PRO LED White Reflector - 24W - Broad Distribution - 3000K	GT19891	29	3030	104.5
G3 PRO LED White Reflector - 24W - Broad Distribution - 3000K	GT19389	28	3030	108.2
G3 PRO LED White Reflector - 24W - Broad Distribution - 4000K	GT19895	29	3260	112.4
G3 PRO LED White Reflector - 24W - Broad Distribution - 4000K	GT19393	28	3260	116.4
G3 PRO LED White Reflector - 24W - SMART - Broad Distribution - 3000K	GT19381	28	3030	108.2
G3 PRO LED White Reflector - 24W - SMART - Broad Distribution - 4000K	GT19385	28	3260	116.4
G3 PRO LED White Reflector - 40W - Broad Distribution - 3000K	GT19892	45	4545	101.0
G3 PRO LED White Reflector - 40W - Broad Distribution - 4000K	GT19896	45	4885	108.6
G3 PRO LED White Reflector - 40W - Narrow Distribution - 3000K	GT19893	45	4515	100.3
G3 PRO LED White Reflector - 40W - Narrow Distribution - 4000K	GT19897	45	4855	107.9
G3 PRO LED White Reflector - 51W - Broad Distribution - 3000K	GT19390	57	5285	92.7

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
G3 PRO LED White Reflector - 51W - Broad Distribution - 4000K	GT19394	57	5685	99.7
G3 PRO LED White Reflector - 51W - Narrow Distribution - 3000K	GT19391	57	5460	95.8
G3 PRO LED White Reflector - 51W - Narrow Distribution - 4000K	GT19395	57	5870	103.0
G3 PRO LED White Reflector - 51W - SMART - Broad Distribution - 3000K	GT19382	57	5285	92.7
G3 PRO LED White Reflector - 51W - SMART - Broad Distribution - 4000K	GT19386	57	5685	99.7
G3 PRO LED White Reflector - 51W - SMART - Narrow Distribution - 3000K	GT19383	57	5460	95.8
G3 PRO LED White Reflector - 51W - SMART - Narrow Distribution - 4000K	GT19387	57	5870	103.0
G3 PRO SURFACE LED Black Reflector - 24W - Broad Distribution - 3000K	GT19899	29	3010	103.8
G3 PRO SURFACE LED Black Reflector - 11W - Broad Distribution - 3000K	GT19898	14	1570	112.1
G3 PRO SURFACE LED Black Reflector - 11W - Broad Distribution - 4000K	GT19902	14	1690	120.7
G3 PRO SURFACE LED Black Reflector - 24W - Broad Distribution - 4000K	GT19903	29	3235	111.6
G3 PRO SURFACE LED Black Reflector - 40W - Broad Distribution - 3000K	GT19900	45	4485	99.7
G3 PRO SURFACE LED Black Reflector - 40W - Broad Distribution - 4000K	GT19904	45	4820	107.1
G3 PRO SURFACE LED Black Reflector - 40W - Narrow Distribution - 3000K	GT19901	45	4420	98.2
G3 PRO SURFACE LED Black Reflector - 40W - Narrow Distribution - 4000K	GT19905	45	4755	105.7
G3 PRO SURFACE LED White Reflector - 11W - Broad Distribution - 3000K	GT19890	14	1580	112.9
G3 PRO SURFACE LED White Reflector - 11W - Broad Distribution - 4000K	GT19894	14	1700	121.4
G3 PRO SURFACE LED White Reflector - 24W - Broad Distribution - 3000K	GT19891	29	3030	104.5
G3 PRO SURFACE LED White Reflector - 24W - Broad Distribution - 4000K	GT19895	29	3260	112.4
G3 PRO SURFACE LED White Reflector - 40W - Broad Distribution - 3000K	GT19892	45	4545	101.0
G3 PRO SURFACE LED White Reflector - 40W - Broad Distribution - 4000K	GT19896	45	4885	108.6
G3 PRO SURFACE LED White Reflector - 40W - Narrow Distribution - 3000K	GT19893	45	4515	100.3
G3 PRO SURFACE LED White Reflector - 40W - Narrow Distribution - 4000K	GT19897	45	4855	107.9
G4 LED Area Lens - 11W - 4000K	GF19144	13	1535	118.1
G4 LED Area Lens - 11W - Ligature Resistant - 4000K	GF19520	13	1370	105.4
G4 LED Area Lens - 22W - 4000K	GF19145	26	2730	105.0
G4 LED Area Lens - 22W - Ligature Resistant - 4000K	GF19251	26	2435	93.7
G4 LED Area Lens - 22W - SMART - 4000K	GF19143	26	2730	105.0
G4 LED Corridor Lens - 11W - 4000K	GF19141	13	1450	111.5
G4 LED Corridor Lens - 11W - Ligature Resistant - 4000K	GF19522	13	1310	100.8
G4 LED Corridor Lens - 22W - 4000K	GF19142	26	2580	99.2
G4 LED Corridor Lens - 22W - Ligature Resistant - 4000K	GF19523	26	2330	89.6
G4 LED Corridor Lens - 22W - SMART - 4000K	GF19140	26	2580	99.2
G4 LED Halo Area Lens - 11W - 4000K	GF19153	13	1500	115.4
G4 LED Halo Area Lens - 22W - 4000K	GF19154	26	2670	102.7
G4 LED Halo Area Lens - 22W - SMART - 4000K	GF19152	26	2670	102.7
G4 LED Halo Corridor Lens - 11W - 4000K	GF19150	13	1400	107.7
G4 LED Halo Corridor Lens - 22W - 4000K	GF19151	26	2490	95.8
G4 LED Halo Corridor Lens - 22W - SMART - 4000K	GF19149	26	2490	95.8
G4 LED Halo Low Glare - 11W - 4000K	GF19156	13	805	61.9
G4 LED Halo Low Glare - 22W - 4000K	GF19157	26	1430	55.0
G4 LED Halo Low Glare - 22W - SMART - 4000K	GF19155	26	1430	55.0
G4 LED IK10 Polycarbonate Area Lens - 22W - 4000K	GF19163	26	2435	93.7
G4 LED IK10 Polycarbonate Corridor Lens - 11W - 4000K	GF19159	13	1310	100.8
G4 LED IK10 Polycarbonate Corridor Lens - 22W - 4000K	GF19160	26	2330	89.6
G4 LED IK10 Polycarbonate Low Glare - 11W - 4000K	GF19165	13	715	55.0
G4 LED IK10 Polycarbonate Low Glare - 22W - 4000K	GF19166	26	1270	48.8
G4 LED IK10 Polycarbonate Area Lens - 11W - 4000K	GF19162	13	1370	105.4
G4 LED Low Glare - 11W - 4000K	GF19147	13	795	61.2
G4 LED Low Glare - 11W - Ligature Resistant - 4000K	GF19524	13	715	55.0
G4 LED Low Glare - 22W - 4000K	GF19148	26	1415	54.4
G4 LED Low Glare - 22W - Ligature Resistant - 4000K	GF19525	26	1270	48.8
G4 LED Low Glare - 22W - SMART - 4000K	GF19146	26	1415	54.4

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
G4 LED Surface 12W - Area Lens - 4000K	GF16171	15	1645	109.7
G4 LED Surface 12W - Corridor Lens - 4000K	GF19168	15	1555	103.7
G4 LED Surface 12W - Low Glare - 4000K	GF19174	15	850	56.7
G4 LED Surface 26W - Area Lens - 4000K	GF19172	32	3050	95.3
G4 LED Surface 26W - Area Lens - SMART - 4000K	GF19170	32	3050	95.3
G4 LED Surface 26W - Corridor Lens - 4000K	GF19169	32	2885	90.2
G4 LED Surface 26W - Corridor Lens - SMART - 4000K	GF19167	32	2885	90.2
G4 LED Surface 26W - Low Glare - 4000K	GF19175	32	1575	49.2
G4 LED Surface 26W - Low Glare - SMART - 4000K	GF19173	32	1575	49.2
Glodome LED - 16W	GLO16483	18	1930	107.2
Glodome LED - 20W	GLO16484	23	2455	106.7
Glodome LED - 26W	GLO15856	29	3055	105.3
GP Linear LED - 46W Faceted Cross Blade	GP16251	52	3535	68.0
GP Linear LED - 46W Prismatic Polycarbonate	GP16253	52	3935	75.7
GP Linear LED - 46W V Blade	GP16249	52	4380	84.2
Grafix - 12W - Medium - 3000K	GXM12M3	14	1335	95.4
Grafix - 12W - Medium - 4000K	GXM12M4	14	1465	104.6
Grafix - 12W - Narrow - 3000K	GXM12N3	14	1365	97.5
Grafix - 12W - Narrow - 4000K	GXM12N4	14	1500	107.1
Grafix - 12W - Wide - 3000K	GXM12W3	14	1240	88.6
Grafix - 12W - Wide - 4000K	GXM12W4	14	1360	97.1
Grafix - 12W - XQUARE NO OPTICS - 3000K	GXM12X3	14	1540	110.0
Grafix - 12W - XQUARE NO OPTICS - 4000K	GXM12X4	14	1640	117.1
Grafix - 12W - XQUARE Q3 OPTICS - 3000K	GXM12X3 + GX19743	14	1270	90.7
Grafix - 12W - XQUARE Q3 OPTICS - 4000K	GXM12X4 + GX19743	14	1395	99.6
Grafix - 12W - XQUARE Q6 OPTICS - 3000K	GXM12X3 + GX19744	14	1225	87.5
Grafix - 12W - XQUARE Q6 OPTICS - 4000K	GXM12X4 + GX19744	14	1345	96.1
Grafix - 12W - XQUARE R1 OPTICS - 3000K	GXM12X3 + GX19742	14	1290	92.1
Grafix - 12W - XQUARE R1 OPTICS - 4000K	GXM12X4 + GX19742	14	1415	101.1
Grafix - 19W - Medium - 3000K	GXM19M3	22	1825	83.0
Grafix - 19W - Medium - 4000K	GXM19M4	22	1945	88.4
Grafix - 19W - Narrow - 3000K	GXM19N3	22	1870	85.0
Grafix - 19W - Narrow - 4000K	GXM19N4	22	1990	90.5
Grafix - 19W - Wide - 3000K	GXM19W3	22	1695	77.0
Grafix - 19W - Wide - 4000K	GXM19W4	22	1805	82.0
Grafix - 19W - XQUARE NO OPTICS - 3000K	GXM19X3	22	2045	93.0
Grafix - 19W - XQUARE NO OPTICS - 4000K	GXM19X4	22	2180	99.1
Grafix - 19W - XQUARE Q3 OPTICS - 3000K	GXM19X3 + GX19743	22	1740	79.1
Grafix - 19W - XQUARE Q3 OPTICS - 4000K	GXM19X4 + GX19743	22	1855	84.3
Grafix - 19W - XQUARE Q6 OPTICS - 3000K	GXM19X3 + GX19744	22	1675	76.1
Grafix - 19W - XQUARE Q6 OPTICS - 4000K	GXM19X4 + GX19744	22	1785	81.1
Grafix - 19W - XQUARE R1 OPTICS - 3000K	GXM19X3 + GX19742	22	1760	80.0
Grafix - 19W - XQUARE R1 OPTICS - 4000K	GXM19X4 + GX19742	22	1875	85.2
Grafix - 27W - Medium - 3000K	GXM27M3	31	2365	76.3
Grafix - 27W - Medium - 4000K	GXM27M4	31	2515	81.1
Grafix - 27W - Narrow - 3000K	GXM27N3	31	2420	78.1
Grafix - 27W - Narrow - 4000K	GXM27N4	31	2575	83.1
Grafix - 27W - Wide - 3000K	GXM27W3	31	2195	70.8
Grafix - 27W - Wide - 4000K	GXM27W4	31	2340	75.5
Grafix - 27W - XQUARE NO OPTICS - 3000K	GXM27X3	31	2195	70.8
Grafix - 27W - XQUARE NO OPTICS - 4000K	GXM27X4	31	2785	89.8
Grafix - 27W - XQUARE Q3 OPTICS - 3000K	GXM27X3 + GX19743	31	2255	72.7
Grafix - 27W - XQUARE Q3 OPTICS - 4000K	GXM27X4 + GX19743	31	2400	77.4

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Grafix - 27W - XQUARE Q6 OPTICS - 3000K	GXM27X3 + GX19744	31	2170	70.0
Grafix - 27W - XQUARE Q6 OPTICS - 4000K	GXM27X4 + GX19744	31	2310	74.5
Grafix - 27W - XQUARE R1 OPTICS - 3000K	GXM27X3 + GX19742	31	2280	73.5
Grafix - 27W - XQUARE R1 OPTICS - 4000K	GXM27X4 + GX19742	31	2430	78.4
Heritage Pendant - Drum 16" - 8W - British Racing Green - 2200K	HP19294VGN	8	630	51.0
Heritage Pendant - Drum 16" - 8W - British Racing Green - 2700K	HP19295VGN	8	806	65.2
Heritage Pendant - Drum 16" - 8W - Ivory - 2200K	HP19294VW	8	630	51.0
Heritage Pendant - Drum 16" - 8W - Ivory - 2700K	HP19295VW	8	806	65.2
Heritage Pendant - Minor 11" - 8W - British Racing Green - Cropped Neck - 2200K	HP19300VGN	8	630	67.3
Heritage Pendant - Minor 11" - 8W - British Racing Green - Cropped Neck - 2700K	HP19301VGN	8	806	86.1
Heritage Pendant - Minor 11" - 8W - British Racing Green - Standard - 2200K	HP19297VGN	8	630	66.6
Heritage Pendant - Minor 11" - 8W - British Racing Green - Standard - 2700K	HP19298VGN	8	806	85.2
Heritage Pendant - Minor 11" - 8W - Ivory - Cropped Neck - 2200K	HP19300VW	8	630	67.3
Heritage Pendant - Minor 11" - 8W - Ivory - Cropped Neck - 2700K	HP19301VW	8	806	86.1
Heritage Pendant - Minor 11" - 8W - Ivory - Standard - 2200K	HP19297VW	8	630	66.6
Heritage Pendant - Minor 11" - 8W - Ivory - Standard - 2700K	HP19298VW	8	806	85.2
Heritage Pendant - Traditional 16" - 8W - British Racing Green - 2200K	HP19291VGN	8	630	60.4
Heritage Pendant - Traditional 16" - 8W - British Racing Green - 2700K	HP19292VGN	8	806	77.3
Heritage Pendant - Traditional 16" - 8W - Ivory - 2200K	HP19291VW	8	630	60.4
Heritage Pendant - Traditional 16" - 8W - Ivory - 2700K	HP19292VW	8	806	77.3
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 17W - 4000K	HB18701 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 17W - SMART - 4000K	HB18695 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 30W - 4000K	HB18702 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 30W - SMART - 4000K	HB18696 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 45W - 4000K	HB18703 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Recessed Continuous 1500mm - 45W - SMART - 4000K	HB18697 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 34W - 4000K	HB18704 + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 34W - SMART - 4000K	HB18698 + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 60W - 4000K	HB18705 + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 60W - SMART - 4000K	HB18699 + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 90W - 4000K	HB18706 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Recessed Continuous 3000mm - 90W - SMART - 4000K	HB18700 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Recessed Individual - 17W - 4000K	HB18679	20	1725	86.3
Hi-Bar Low Glare LED Recessed Individual - 17W - SMART - 4000K	HB18674	20	1725	86.3
Hi-Bar Low Glare LED Recessed Individual - 30W - 4000K	HB18680	35	2975	85.0
Hi-Bar Low Glare LED Recessed Individual - 30W - SMART - 4000K	HB18675	35	2975	85.0
Hi-Bar Low Glare LED Recessed Individual - 45W - 4000K	HB18681	51	4300	84.3
Hi-Bar Low Glare LED Recessed Individual - 45W - SMART - 4000K	HB18676	51	4300	84.3
Hi-Bar Low Glare LED Recessed Left-hand Corner - 17W - 4000K	HB19252	20	1725	86.3
Hi-Bar Low Glare LED Recessed Left-hand Corner - 17W - SMART - 4000K	HB19246	20	1725	86.3
Hi-Bar Low Glare LED Recessed Left-hand Corner - 30W - 4000K	HB19253	35	2975	85.0
Hi-Bar Low Glare LED Recessed Left-hand Corner - 30W - SMART - 4000K	HB19247	35	2795	79.9
Hi-Bar Low Glare LED Recessed Left-hand Corner - 45W - 4000K	HB19254	51	4300	84.3
Hi-Bar Low Glare LED Recessed Left-hand Corner - 45W - SMART - 4000K	HB19248	51	4300	84.3
Hi-Bar Low Glare LED Recessed Right-hand Corner - 17W - 4000K	HB19255	20	1725	86.3
Hi-Bar Low Glare LED Recessed Right-hand Corner - 17W - SMART - 4000K	HB19249	20	1725	86.3
Hi-Bar Low Glare LED Recessed Right-hand Corner - 30W - 4000K	HB19256	35	2975	85.0
Hi-Bar Low Glare LED Recessed Right-hand Corner - 30W - SMART - 4000K	HB19250	35	2795	79.9
Hi-Bar Low Glare LED Recessed Right-hand Corner - 45W - 4000K	HB19257	51	4300	84.3
Hi-Bar Low Glare LED Recessed Right-hand Corner - 45W - SMART - 4000K	HB19251	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - 4000K	HB18716 + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - 4000K	HB18716 + HB18668	40	3450	86.3



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - 4000K - With Uplight	HB18716UL + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - 4000K - With Uplight	HB18716UL + HB18668	40	3000	75.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - 4000K	HB18713 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - 4000K	HB18713 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - 4000K - With Uplight	HB18713UL + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - 4000K - With Uplight	HB18713UL + HB18668	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K	HB18707 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K	HB18707 + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K - With Uplight	HB18707UL + HB18668	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K - With Uplight	HB18707UL + HB18668	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - 4000K	HB18714 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - 4000K	HB18714 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - 4000K - With Uplight	HB18714UL + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - 4000K - With Uplight	HB18714UL + HB18668	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K	HB18708 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K	HB18708 + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K - With Uplight	HB18708UL + HB18668	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K - With Uplight	HB18708UL + HB18668	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - 4000K	HB18715 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - 4000K	HB18715 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - 4000K - With Uplight	HB18715UL + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - 4000K - With Uplight	HB18715UL + HB18668	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K	HB18709 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K	HB18709 + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K - With Uplight	HB18709UL + HB18668	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K - With Uplight	HB18709UL + HB18668	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K	HB18710 + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K	HB18710 + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K - With Uplight	HB18710UL + HB18668	40	3450	86.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K - With Uplight	HB18710UL + HB18668	40	3000	75.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - 4000K	HB18717 + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - 4000K	HB18717 + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - 4000K - With Uplight	HB18717UL + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - 4000K - With Uplight	HB18717UL + HB18668	70	5200	74.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K	HB18711 + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K	HB18711 + HB18668	70	5950	85.0



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K - With Uplight	HB18711UL + HB18668	70	5950	85.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K - With Uplight	HB18711UL + HB18668	70	5200	74.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - 4000K	HB18718 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - 4000K	HB18718 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - 4000K - With Uplight	HB18718UL + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - 4000K - With Uplight	HB18718UL + HB18668	102	7040	69.0
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K	HB18712 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K	HB18712 + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K - With Uplight	HB18712UL + HB18668	102	8600	84.3
Hi-Bar Low Glare LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K - With Uplight	HB18712UL + HB18668	102	7040	69.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - 4000K	HB18692	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - 4000K	HB18692	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - 4000K - With Uplight	HB18692UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - 4000K - With Uplight	HB18692UL	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - SMART - 4000K	HB18686	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - SMART - 4000K	HB18686	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - SMART - 4000K - With Uplight	HB18686UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 17W - SMART - 4000K - With Uplight	HB18686UL	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - 4000K	HB18693	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - 4000K	HB18693	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - 4000K - With Uplight	HB18693UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - 4000K - With Uplight	HB18693UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - SMART - 4000K	HB18687	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - SMART - 4000K	HB18687	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - SMART - 4000K - With Uplight	HB18687UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 30W - SMART - 4000K - With Uplight	HB18687UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - 4000K	HB18694	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - 4000K	HB18694	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - 4000K - With Uplight	HB18694UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - 4000K - With Uplight	HB18694UL	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - SMART - 4000K	HB18688	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - SMART - 4000K	HB18688	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - SMART - 4000K - With Uplight	HB18688UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Individual - 45W - SMART - 4000K - With Uplight	HB18688UL	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - 4000K	HB19240	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - 4000K	HB19240	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - 4000K - With Uplight	HB19240UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - 4000K - With Uplight	HB19240UL	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K	HB19234	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K	HB19234	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K - With Uplight	HB19234UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K - With Uplight	HB19234UL	20	1500	75.0

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - 4000K	HB19241	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - 4000K	HB19241	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - 4000K - With Uplight	HB19241UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - 4000K - With Uplight	HB19241UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K	HB19235	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K	HB19235	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K - With Uplight	HB19235UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K - With Uplight	HB19235UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - 4000K	HB19242	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - 4000K	HB19242	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - 4000K - With Uplight	HB19242UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - 4000K - With Uplight	HB19242UL	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K	HB19236	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K	HB19236	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K - With Uplight	HB19236UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K - With Uplight	HB19236UL	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - 4000K	HB19243UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - 4000K	HB19243UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - 4000K - With Uplight	HB19243UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - 4000K - With Uplight	HB19243UL	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K	HB19237	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K	HB19237	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K - With Uplight	HB19237UL	20	1725	86.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K - With Uplight	HB19237UL	20	1500	75.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - 4000K	HB19244	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - 4000K	HB19244	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - 4000K - With Uplight	HB19244UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - 4000K - With Uplight	HB19244UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K	HB19238	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K	HB19238	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K - With Uplight	HB19238UL	35	2975	85.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K - With Uplight	HB19238UL	35	2600	74.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - 4000K	HB19245	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - 4000K	HB19245	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - 4000K - With Uplight	HB19245UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - 4000K - With Uplight	HB19245UL	51	3520	69.0
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K	HB19239	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K	HB19239	51	4300	84.3

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K - With Uplight	HB19239UL	51	4300	84.3
Hi-Bar Low Glare LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K - With Uplight	HB19239UL	51	3520	69.0
Hi-Bar Opal LED Recessed Continuous 1500mm - 17W - 4000K	HB18701 + HB18667	20	2190	109.5
Hi-Bar Opal LED Recessed Continuous 1500mm - 17W - SMART - 4000K	HB18695 + HB18667	20	2190	109.5
Hi-Bar Opal LED Recessed Continuous 1500mm - 30W - 4000K	HB18702 + HB18667	35	3775	107.9
Hi-Bar Opal LED Recessed Continuous 1500mm - 30W - SMART - 4000K	HB18696 + HB18667	35	3775	107.9
Hi-Bar Opal LED Recessed Continuous 1500mm - 45W - 4000K	HB18703 + HB18667	51	5455	107.0
Hi-Bar Opal LED Recessed Continuous 1500mm - 45W - SMART - 4000K	HB18697 + HB18667	51	5455	107.0
Hi-Bar Opal LED Recessed Continuous 3000mm - 34W - 4000K	HB18704 + HB18667	40	4380	109.5
Hi-Bar Opal LED Recessed Continuous 3000mm - 34W - SMART - 4000K	HB18698 + HB18667	40	4380	109.5
Hi-Bar Opal LED Recessed Continuous 3000mm - 60W - 4000K	HB18705 + HB18667	70	7550	107.9
Hi-Bar Opal LED Recessed Continuous 3000mm - 60W - SMART - 4000K	HB18699 + HB18667	70	7550	107.9
Hi-Bar Opal LED Recessed Continuous 3000mm - 90W - 4000K	HB18706 + HB18667	102	10910	107.0
Hi-Bar Opal LED Recessed Continuous 3000mm - 90W - SMART - 4000K	HB18700 + HB18667	102	10910	107.0
Hi-Bar Opal LED Recessed Individual - 17W - 4000K	HB18677	20	2190	109.5
Hi-Bar Opal LED Recessed Individual - 17W - SMART - 4000K	HB18671	20	2190	109.5
Hi-Bar Opal LED Recessed Individual - 30W - 4000K	HB18678	35	3775	107.9
Hi-Bar Opal LED Recessed Individual - 30W - SMART - 4000K	HB18672	35	3775	107.9
Hi-Bar Opal LED Recessed Individual - 45W - 4000K	HB18679	51	5455	107.0
Hi-Bar Opal LED Recessed Individual - 45W - SMART - 4000K	HB18673	51	5455	107.0
Hi-Bar Opal LED Recessed Left-hand Corner - 17W - 4000K	HB19228	20	2190	109.5
Hi-Bar Opal LED Recessed Left-hand Corner - 17W - SMART - 4000K	HB19222	20	2190	109.5
Hi-Bar Opal LED Recessed Left-hand Corner - 30W - 4000K	HB19229	35	3775	107.9
Hi-Bar Opal LED Recessed Left-hand Corner - 30W - SMART - 4000K	HB19223	35	3775	107.9
Hi-Bar Opal LED Recessed Left-hand Corner - 45W - 4000K	HB19230	51	5455	107.0
Hi-Bar Opal LED Recessed Left-hand Corner - 45W - SMART - 4000K	HB19224	51	5455	107.0
Hi-Bar Opal LED Recessed Right-hand Corner - 17W - 4000K	HB19231	20	2190	109.5
Hi-Bar Opal LED Recessed Right-hand Corner - 17W - SMART - 4000K	HB19225	20	2190	109.5
Hi-Bar Opal LED Recessed Right-hand Corner - 30W - 4000K	HB19232	35	3775	107.9
Hi-Bar Opal LED Recessed Right-hand Corner - 30W - SMART - 4000K	HB19226	35	3775	107.9
Hi-Bar Opal LED Recessed Right-hand Corner - 45W - 4000K	HB19233	51	5455	107.0
Hi-Bar Opal LED Recessed Right-hand Corner - 45W - SMART - 4000K	HB19227	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - 4000K	HB18713 + HB18667	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - 4000K	HB18713 + HB18667	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - 4000K - With Uplight	HB18713UL + HB18667	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - 4000K - With Uplight	HB18713UL + HB18667	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K	HB18707 + HB18667	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K	HB18707 + HB18667	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K - With Uplight	HB18707UL + HB18667	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 17W - SMART - 4000K - With Uplight	HB18707UL + HB18667	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - 4000K	HB18714 + HB18667	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - 4000K	HB18714 + HB18667	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - 4000K - With Uplight	HB18714UL + HB18667	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - 4000K - With Uplight	HB18714UL + HB18667	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K	HB18708 + HB18667	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K	HB18708 + HB18667	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K - With Uplight	HB18708UL + HB18667	35	3015	86.1

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 30W - SMART - 4000K - With Uplight	HB18708UL + HB18667	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - 4000K	HB18715 + HB18667	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - 4000K	HB18715 + HB18667	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - 4000K - With Uplight	HB18715UL + HB18667	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - 4000K - With Uplight	HB18715UL + HB18667	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K	HB18709 + HB18667	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K	HB18709 + HB18667	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K - With Uplight	HB18709UL + HB18667	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 1500mm - 45W - SMART - 4000K - With Uplight	HB18709UL + HB18667	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - 4000K	HB18716 + HB18667	40	4380	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - 4000K	HB18716 + HB18667	40	4380	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - 4000K - With Uplight	HB18716UL + HB18667	40	3470	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - 4000K - With Uplight	HB18716UL + HB18667	40	3470	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K	HB18710 + HB18667	40	4380	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K	HB18710 + HB18667	40	4380	109.5
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K - With Uplight	HB18710UL + HB18667	40	3470	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 34W - SMART - 4000K - With Uplight	HB18710UL + HB18667	40	3470	86.8
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - 4000K	HB18717 + HB18667	70	7550	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - 4000K	HB18717 + HB18667	70	7550	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - 4000K - With Uplight	HB18717UL + HB18667	70	6030	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - 4000K - With Uplight	HB18717UL + HB18667	70	6030	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K	HB18711 + HB18667	70	7550	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K	HB18711 + HB18667	70	7550	107.9
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K - With Uplight	HB18711UL + HB18667	70	6030	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 60W - SMART - 4000K - With Uplight	HB18711UL + HB18667	70	6030	86.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - 4000K	HB18718 + HB18667	102	10910	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - 4000K	HB18718 + HB18667	102	10910	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - 4000K - With Uplight	HB18718UL + HB18667	102	8170	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - 4000K - With Uplight	HB18718UL + HB18667	102	8170	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K	HB18712 + HB18667	102	10910	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K	HB18712 + HB18667	102	10910	107.0
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K - With Uplight	HB18712UL + HB18667	102	8170	80.1
Hi-Bar Opal LED Surface / Suspended Continuous 3000mm - 90W - SMART - 4000K - With Uplight	HB18712UL + HB18667	102	8170	80.1
Hi-Bar Opal LED Surface / Suspended Individual - 17W - 4000K	HB18689	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Individual - 17W - 4000K	HB18689	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Individual - 17W - 4000K - With Uplight	HB18689UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Individual - 17W - 4000K - With Uplight	HB18689UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Individual - 17W - SMART - 4000K	HB18683	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Individual - 17W - SMART - 4000K	HB18683	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Individual - 17W - SMART - 4000K - With Uplight	HB18683UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Individual - 17W - SMART - 4000K - With Uplight	HB18683UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Individual - 30W - 4000K	HB18690	35	3775	107.9

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Opal LED Surface / Suspended Individual - 30W - 4000K	HB18690	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Individual - 30W - 4000K - With Uplight	HB18690UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Individual - 30W - 4000K - With Uplight	HB18690UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Individual - 30W - SMART - 4000K	HB18684	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Individual - 30W - SMART - 4000K	HB18684	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Individual - 30W - SMART - 4000K - With Uplight	HB18684UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Individual - 30W - SMART - 4000K - With Uplight	HB18684UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Individual - 45W - 4000K	HB18691	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Individual - 45W - 4000K	HB18691	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Individual - 45W - 4000K - With Uplight	HB18691UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Individual - 45W - 4000K - With Uplight	HB18691UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Individual - 45W - SMART - 4000K	HB18685	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Individual - 45W - SMART - 4000K	HB18685	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Individual - 45W - SMART - 4000K - With Uplight	HB18685UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Individual - 45W - SMART - 4000K - With Uplight	HB18685UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - 4000K	HB19216	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - 4000K	HB19216	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - 4000K - With Uplight	HB19216UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - 4000K - With Uplight	HB19216UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K	HB19210	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K	HB19210	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K - With Uplight	HB19210UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 17W - SMART - 4000K - With Uplight	HB19210UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - 4000K	HB19217	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - 4000K	HB19217	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - 4000K - With Uplight	HB19217UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - 4000K - With Uplight	HB19217UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K	HB19211	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K	HB19211	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K - With Uplight	HB19211UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 30W - SMART - 4000K - With Uplight	HB19211UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - 4000K	HB19218	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - 4000K	HB19218	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - 4000K - With Uplight	HB19218UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - 4000K - With Uplight	HB19218UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K	HB19212	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K	HB19212	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K - With Uplight	HB19212UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Left-hand Corner - 45W - SMART - 4000K - With Uplight	HB19212UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - 4000K	HB19219	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - 4000K	HB19219	20	2190	109.5
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - 4000K - With Uplight	HB19219UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - 4000K - With Uplight	HB19219UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K	HB19213	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K	HB19213	20	2190	109.5



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K - With Uplight	HB19313UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 17W - SMART - 4000K - With Uplight	HB19313UL	20	1735	86.8
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - 4000K	HB19220	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - 4000K	HB19220	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - 4000K - With Uplight	HB19220UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - 4000K - With Uplight	HB19220UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K	HB19214	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K	HB19214	35	3775	107.9
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K - With Uplight	HB19214UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 30W - SMART - 4000K - With Uplight	HB19214UL	35	3015	86.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - 4000K	HB19221	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - 4000K	HB19221	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - 4000K - With Uplight	HB19221UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - 4000K - With Uplight	HB19221UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K	HB19215	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K	HB19215	51	5455	107.0
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K - With Uplight	HB19215UL	51	4085	80.1
Hi-Bar Opal LED Surface / Suspended Right-hand Corner - 45W - SMART - 4000K - With Uplight	HB19215UL	51	4085	80.1
High Dependency Linear - 46W	HD16245	52	3345	64.3
High Dependency Modular - 112W	HD18770	123	8760	71.2
Hi-Style GLO - 1x40W - 3000K	HI12319	45	3500	62.2
Hi-Style GLO - 1x40W - SMART - 3000K	HI12323	45	3500	62.2
Hi-Style GLO - 1x55W - 3000K	HI12320	63	4800	49.5
Hi-Style GLO - 1x55W - SMART - 3000K	HI12324	63	4800	49.5
Hi-Style GLO ECO - 2x13W - 4000K	HI14775	29	2300	77.7
Hi-Style GLO ECO - 2x13W - SMART - 4000K	HI14777	29	3300	111.5
Hi-Style GLO ECO - 2x20W - 4000K	HI14776	44	2300	49.7
Hi-Style GLO ECO - 2x20W - SMART - 4000K	HI14778	44	3300	71.3
Hi-Style LED - 16W	HI19723	19	2670	140.5
Hi-Style LED - 24W	HI19724	29	4040	139.3
Hi-Style LED - 34W	HI19725	40	5300	132.5
Hi-Style LED LG7 - 16W - ColourControl	HI18532CC	18	2110	117.2
Hi-Style LED LG7 - 16W - SMART - ColourActive	HI18526CA	18	2110	117.2
Hi-Style LED LG7 - 24W - ColourControl	HI18533CC	27	3080	114.1
Hi-Style LED LG7 - 24W - SMART - ColourActive	HI18527CA	27	3080	114.1
Hi-Style LED LG7 - 34W - ColourControl	HI19133CC	38	4425	116.4
Hi-Style LED LG7 - 34W - SMART - ColourActive	HI19132CA	38	4425	116.4
Hi-Style LED Opal - 16W	HI19729	19	2585	136.1
Hi-Style LED Opal - 16W - ColourControl	HI18529CC	18	2235	124.2
Hi-Style LED Opal - 16W - SMART - ColourActive	HI18523CA	18	2235	124.2
Hi-Style LED Opal - 24W	HI19730	28	3885	138.8
Hi-Style LED Opal - 24W - ColourControl	HI18530CC	27	3225	119.4
Hi-Style LED Opal - 24W - SMART - ColourActive	HI18524CA	27	3225	119.4
Hi-Style LED Opal - 34W	HI19731	40	5195	129.9
Hi-Style LED Opal - 34W - ColourControl	HI19131CC	38	4635	122.0
Hi-Style LED Opal - 34W - SMART - ColourActive	HI19130CA	38	4635	122.0
Hi-Style LED OPAL 1200 X 600 - 36W	HI19829	41	5940	144.9

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Hi-Style LED OPAL 1200 X 600 - 36W - SMART	HI19826	41	5940	144.9
Hi-Style LED OPAL 1200 X 600 - 48W	HI19830	54	7595	140.6
Hi-Style LED OPAL 1200 X 600 - 48W - SMART	HI19827	54	7595	140.6
Hi-Style LED OPAL 1200 X 600 - 64W	HI19831	72	9680	134.4
Hi-Style LED OPAL 1200 X 600 - 64W - SMART	HI19828	72	9680	134.4
Hi-Style LED Opal SMART - 16W	HI19726	19	2585	136.1
Hi-Style LED Opal SMART - 24W	HI19727	28	3885	138.8
Hi-Style LED Opal SMART - 34W	HI19728	40	5195	129.9
Hi-Style LED SMART - 16W	HI19720	19	2670	140.5
Hi-Style LED SMART - 24W	HI19721	28	4040	144.3
Hi-Style LED SMART - 34W	HI19722	40	5300	132.5
Hi-Style PRO - 1x40W - 3000K	HI12303	45	3500	59.9
Hi-Style PRO - 1x40W - SMART - 3000K	HI12305	45	3500	59.9
Hi-Style PRO - 1x55W - 3000K	HI12304	63	4800	48.8
Hi-Style PRO - 1x55W - SMART - 3000K	HI12306	63	4800	48.8
Hi-Style PRO Daylight - 1x55W - 6500K	HI12996	63	4550	39.7
Hi-Style PRO Daylight - 1x55W - SMART - 6500K	HI13240	63	4550	39.7
Hi-Style PRO Daylight - 2x40W - 6500K	HI12997	89	6650	37.4
Hi-Style PRO Daylight - 2x40W - SMART - 6500K	HI13241	89	6650	37.4
Hi-Style PRO ECO - 2x13W - 4000K	HI14771	29	2300	76.9
Hi-Style PRO ECO - 2x13W - SMART - 4000K	HI14773	29	3300	110.4
Hi-Style PRO ECO - 2x20W - 4000K	HI14772	44	2300	48.6
Hi-Style PRO ECO - 2x20W - SMART - 4000K	HI14774	44	3300	69.8
Hyline 1200x300 - 23W - 4000K	HY18791	27	3085	114.3
Hyline 1200x300 - 23W - SMART - 4000K	HY18776	27	3085	114.3
Hyline 1200x300 - 29W - 4000K	HY18793	32	3855	120.5
Hyline 1200x300 - 29W - SMART - 4000K	HY18778	32	3855	120.5
Hyline 1200x300 - 37W - 4000K	HY18794	41	4840	118.0
Hyline 1200x300 - 37W - SMART - 4000K	HY18779	41	4840	118.0
Hyline 600x600 - 23W - 4000K	HY18786	27	2845	105.4
Hyline 600x600 - 23W - SMART - 4000K	HY18771	27	2845	105.4
Hyline 600x600 - 29W - 4000K	HY18788	32	3635	113.6
Hyline 600x600 - 29W - SMART - 4000K	HY18773	32	3635	113.6
Hyline 600x600 - 37W - 4000K	HY18789	41	4580	111.7
Hyline 600x600 - 37W - SMART - 4000K	HY18774	41	4580	111.7
Jubilee - 1x28W	JUB13061	31	2600	74.6
Jubilee - 1x35W	JUB13065	38	3300	69.5
Jubilee - 1x49W	JUB13067	53	4300	61.7
Jubilee - 2x14W	JUB13612	32	2400	60.8
Jubilee - 2x28W	JUB13062	61	5200	63.9
Jubilee - 2x35W	JUB13066	76	6600	71.2
Jubilee - 2x49W	JUB13068	106	8600	60.0
Jubilee LED - 14W	JUB19636	18	2575	143.1
Jubilee LED - 18W	JUB16947	22	3175	144.3
Jubilee LED - 21W	JUB16506	25	3545	141.8
Jubilee LED - 30W	JUB16507	35	5010	143.1
Jubilee LED - 30W - ColourControl	JUB18804CC	34	3481	102.4
Jubilee LED - 30W - SMART - ColourActive	JUB18801CA	34	3480	102.4
Jubilee LED - 31W	JUB16948	35	5270	150.6
Jubilee LED - 37W - ColourControl	JUB18805CC	42	4175	99.4
Jubilee LED - 37W - SMART - ColourActive	JUB18802CA	42	4175	99.4
Jubilee LED - 43W	JUB16508	50	6915	138.3
Jubilee LED - 51W	JUB16509	58	8065	139.1



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Jubilee LED SMART - 14W	JUB19635	18	2575	143.1
Jubilee LED SMART - 18W	JUB16945	22	3175	144.3
Jubilee LED SMART - 21W	JUB16502	25	3545	141.8
Jubilee LED SMART - 30W	JUB16503	35	5010	143.1
Jubilee LED SMART - 31W	JUB16946	35	5270	150.6
Jubilee LED SMART - 43W	JUB16504	50	6915	138.3
Jubilee LED SMART - 51W	JUB16505	58	8065	139.1
Jubilee SMART - 1x28W	JUB13077	30.5	2600	75.9
Jubilee SMART - 1x35W	JUB13079	39	3300	67.7
Jubilee SMART - 1x49W	JUB13081	53	4300	61.7
Jubilee SMART - 2x14W	JUB13616	30.5	2400	63.7
Jubilee SMART - 2x28W	JUB13078	60.5	5200	64.5
Jubilee SMART - 2x35W	JUB13080	74.5	6600	72.6
Jubilee SMART - 2x49W	JUB13082	105.5	8600	60.3
Jubilee XL - 1x28W	JUB13069	31	2600	79.7
Jubilee XL - 1x35W	JUB13073	38	3300	75.6
Jubilee XL - 1x49W	JUB13075	53	4300	66.5
Jubilee XL - 2x28W	JUB13070	61	5200	65.6
Jubilee XL - 2x35W	JUB13074	76	6600	73.8
Jubilee XL - 2x49W	JUB13076	106	8600	64.9
Jubilee XL LED - 14W	JUB19631	18	2635	146.4
Jubilee XL LED - 18W	JUB16951	22	3210	145.9
Jubilee XL LED - 21W	JUB16697	25	3625	145.0
Jubilee XL LED - 30W	JUB16698	35	5105	145.9
Jubilee XL LED - 31W	JUB16952	35	5315	151.9
Jubilee XL LED - 43W	JUB16699	50	7120	142.4
Jubilee XL LED SMART - 14W	JUB19632	18	2635	146.4
Jubilee XL LED SMART - 18W	JUB16949	22	3210	145.9
Jubilee XL LED SMART - 21W	JUB16693	25	3625	145.0
Jubilee XL LED SMART - 30W	JUB16694	35	5105	145.9
Jubilee XL LED SMART - 31W	JUB16950	35	5315	151.9
Jubilee XL LED SMART - 43W	JUB16695	50	7120	142.4
Jubilee XL SMART - 1x28W	JUB13083	30.5	2600	81.0
Jubilee XL SMART - 1x35W	JUB13085	39	3300	73.6
Jubilee XL SMART - 1x49W	JUB13087	53	4300	66.5
Jubilee XL SMART - 2x28W	JUB13084	60.5	5200	66.2
Jubilee XL SMART - 2x35W	JUB13086	74.5	6600	75.3
Jubilee XL SMART - 2x49W	JUB13088	105.5	8600	65.2
Juno A - 31W	JUN17672	36	4320	120.0
Juno A - 52W	JUN17673	61	6825	111.9
Juno B - 101W - Asymmetric Distribution	JUN19659	110	11965	108.8
Juno B - 101W - Symmetric Distribution	JUN19658	110	12080	109.8
Juno B - 37W - Asymmetric Distribution	JUN19202	44	5365	121.9
Juno B - 37W - Symmetric Distribution	JUN19200	44	5385	122.4
Juno B - 78W - Asymmetric Distribution	JUN19203	83	10025	120.8
Juno B - 78W - Symmetric Distribution	JUN19201	83	10065	121.3
Juno C - 52W	JUN17678	61	6360	104.3
Juno C - 52W SMART	JUN17676	61	6360	104.3
Juno C - 78W	JUN17679	89	9155	102.9
Juno C - 78W SMART	JUN17676	89	9155	102.9
Juno D - 132W - Asymmetric Distribution	JUN18635	144	16280	113.1
Juno D - 166W - Asymmetric Distribution	JUN18636	180	19750	109.7
Juno D - 177W - Symmetric Distribution	JUN18631	197	24020	121.9

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Juno D - 246W - Symmetric Distribution	JUN18632	265	31920	120.5
Juno D - 326W - Symmetric Distribution	JUN18633	350	39940	114.1
Juno D - 99W - Asymmetric Distribution	JUN18634	108	12515	115.9
Kanby EVO - 15W - Low Glare	KE18697	19	2280	120.0
Kanby EVO - 15W - Opal	KE18959	19	2190	115.3
Kanby EVO - 15W - SMART - Low Glare	KE18951	19	2280	120.0
Kanby EVO - 15W - SMART - Opal	KE18943	19	2190	115.3
Kanby EVO - 22W - Low Glare	KE18972	25	3470	138.8
Kanby EVO - 22W - Opal	KE18964	25	3330	133.2
Kanby EVO - 22W - SMART - Low Glare	KE18956	25	3470	138.8
Kanby EVO - 22W - SMART - Opal	KE18948	25	3330	133.2
Kanby EVO - 26W - Low Glare	KE18968	29	3860	133.1
Kanby EVO - 26W - Opal	KE18960	29	3705	127.8
Kanby EVO - 26W - SMART - Low Glare	KE18952	29	3860	133.1
Kanby EVO - 26W - SMART - Opal	KE18944	29	3705	127.8
Kanby EVO - 36W - Low Glare	KE18973	41	5490	133.9
Kanby EVO - 36W - Opal	KE18965	41	5270	128.5
Kanby EVO - 36W - SMART - Low Glare	KE18957	41	5490	133.9
Kanby EVO - 36W - SMART - Opal	KE18949	41	5270	128.5
Kanby EVO - 43W - Low Glare	KE18974	49	6510	132.9
Kanby EVO - 43W - Opal	KE18966	49	6250	127.6
Kanby EVO - 43W - SMART - Low Glare	KE18958	49	6510	132.9
Kanby EVO - 43W - SMART - Opal	KE18950	49	6250	127.6
Kanby LED Controller - 21W - Narrow Body	KB17607	25	3555	142.2
Kanby LED Controller - 28W - Narrow Body	KB16105	33	4590	139.1
Kanby LED Controller - 30W - ColourControl	KB18816CC	34	4075	119.9
Kanby LED Controller - 30W - SMART - ColourActive	KB18813CA	34	4075	119.9
Kanby LED Controller - 37W - ColourControl	KB18817CC	42	4845	115.4
Kanby LED Controller - 37W - Narrow Body	KB16106	43	5860	136.3
Kanby LED Controller - 37W - SMART - ColourActive	KB18814CA	42	4845	115.4
Kanby LED Controller - 49W - Wide Body	KB16101	57	7670	134.6
Kanby LED Controller - 63W - Wide Body	KB16102	71	9465	133.3
Kanby LED Controller SMART - 21W - Narrow Body	KB17606	25	3555	142.2
Kanby LED Controller SMART - 28W - Narrow Body	KB16107	33	4590	139.1
Kanby LED Controller SMART - 37W - Narrow Body	KB16108	43	5860	136.3
Kanby LED Controller SMART - 49W - Wide Body	KB16103	57	7670	134.6
Kanby LED Controller SMART - 63W - Wide Body	KB16104	71	9465	133.3
Kanby LED Mirror Broad - 22W	KB15870	26	3890	149.6
Kanby LED Mirror Broad - 30W	KB15871	35	5355	153.0
Kanby LED Mirror Broad - 52W	KB15872	59	8460	143.4
Kanby LED Mirror Broad SMART - 22W	KB15876	26	3890	149.6
Kanby LED Mirror Broad SMART - 30W	KB15877	35	5355	153.0
Kanby LED Mirror Broad SMART - 52W	KB15878	59	8460	143.4
Kanby LED Mirror Narrow - 22W	KB15873	26	3790	145.8
Kanby LED Mirror Narrow - 30W	KB15874	35	5110	146.0
Kanby LED Mirror Narrow - 52W	KB15875	59	8270	140.2
Kanby LED Mirror Narrow SMART - 22W	KB15879	26	3790	145.8
Kanby LED Mirror Narrow SMART - 30W	KB15880	35	5110	146.0
Kanby LED Mirror Narrow SMART - 52W	KB15881	59	8270	140.2
Kanby MAX Broad - 22W - 4000K	KB19646	25	3920	156.8
Kanby MAX Broad - 22W - SMART - 4000K	KB19640	25	3920	156.8
Kanby MAX Broad - 30W - 4000K	KB19647	34	5355	157.5
Kanby MAX Broad - 30W - SMART - 4000K	KB19641	34	5355	157.5

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Kanby MAX Broad - 52W - 4000K	KB19648	59	9115	154.5
Kanby MAX Broad - 52W - SMART - 4000K	KB19642	59	9115	154.5
Kanby MAX Narrow - 22W - 4000K	KB19649	25	3840	153.6
Kanby MAX Narrow - 22W - SMART - 4000K	KB19643	25	3840	153.6
Kanby MAX Narrow - 30W - 4000K	KB19650	34	5240	154.1
Kanby MAX Narrow - 30W - SMART - 4000K	KB19644	34	5240	154.1
Kanby MAX Narrow - 52W - 4000K	KB19651	59	8925	151.3
Kanby MAX Narrow - 52W - SMART - 4000K	KB19645	59	8925	151.3
Kanby PRO - 15W - Low Glare	KP18935	19	2280	120.0
Kanby PRO - 15W - Opal	KP18927	19	2190	115.3
Kanby PRO - 15W - SMART - Low Glare	KP18919	19	2280	120.0
Kanby PRO - 15W - SMART - Opal	KP18911	19	2190	115.3
Kanby PRO - 22W - Low Glare	KP18940	25	3470	138.8
Kanby PRO - 22W - Opal	KP18932	25	3330	133.2
Kanby PRO - 22W - SMART - Low Glare	KP18924	25	3470	138.8
Kanby PRO - 22W - SMART - Opal	KP18916	25	3330	133.2
Kanby PRO - 26W - Low Glare	KP18936	29	3860	133.1
Kanby PRO - 26W - Opal	KP18928	29	3705	127.8
Kanby PRO - 26W - SMART - Low Glare	KP18920	29	3860	133.1
Kanby PRO - 26W - SMART - Opal	KP18912	29	3705	127.8
Kanby PRO - 36W - Low Glare	KP18941	41	5490	133.9
Kanby PRO - 36W - Opal	KP18933	41	5270	128.5
Kanby PRO - 36W - SMART - Low Glare	KP18925	41	5490	133.9
Kanby PRO - 36W - SMART - Opal	KP18917	41	5270	128.5
Kanby PRO - 43W - Low Glare	KP18942	49	6510	132.9
Kanby PRO - 43W - Opal	KP18934	49	6250	127.6
Kanby PRO - 43W - SMART - Low Glare	KP18926	49	6510	132.9
Kanby PRO - 43W - SMART - Opal	KP18918	49	6250	127.6
Kanby T5 Acrylic Controller - 28W	KB10848	31	2600	72.1
Kanby T5 Acrylic Controller - 2x28W	KB10849	61	5200	69.9
Kanby T5 Acrylic Controller - 2x35W	KB10851	76	6600	74.7
Kanby T5 Acrylic Controller - 2x49W	KB10855	106	8600	69.8
Kanby T5 Acrylic Controller - 35W	KB10850	38	3300	82.5
Kanby T5 Acrylic Controller - 49W	KB10854	53	4300	77.9
Kanby T5 Batten - 1x28W	KB10822	31	2600	85.5
Kanby T5 Batten - 1x35W	KB10824	38	3300	93.8
Kanby T5 Batten - 1x49W	KB10828	53	4300	83.6
Kanby T5 Batten - 1x54W	KB10826	57	4450	80.4
Kanby T5 Batten - 2x28W	KB10823	61	5200	83.5
Kanby T5 Batten - 2x35W	KB10825	76	6600	84.2
Kanby T5 Batten - 2x49W	KB10829	106	8600	80.3
Kanby T5 Batten - 2x54W	KB10827	114	8900	61.7
Kanby T5 Batten SMART - 1x35W	KB13377	39	3300	91.4
Kanby T5 Batten SMART - 2x35W	KB13254	74.5	6600	85.9
Kanby T5 Mirror Reflector - 1x49W	KB10844	53	4300	77.9
Kanby T5 Mirror Reflector - 1x80W	KB10846	86	6450	72.8
Kanby T5 Mirror Reflector - 2x49W	KB10845	106	8600	76.3
Kanby T5 Mirror Reflector - 2x80W	KB12027	171	12900	70.9
Kanby T5 Mirror Reflector SMART - 2x49W	KB13396	105.5	8600	76.6
Kanby T5 Mirror Reflector SMART - 2x80W	KB13397	167	12900	72.6
Kanby T5 Polycarbonate Controller - 28W	KB10856	31	2600	70.5
Kanby T5 Polycarbonate Controller - 2x28W	KB10857	61	5200	63.9
Kanby T5 Polycarbonate Controller - 2x35W	KB10859	76	6600	71.2

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Kanby T5 Polycarbonate Controller - 2x49W	KB10863	106	8600	64.1
Kanby T5 Polycarbonate Controller - 35W	KB10858	38	3300	75.6
Kanby T5 Polycarbonate Controller - 49W	KB10862	53	4300	73.0
Kanby T5 Polycarbonate Controller SMART - 2x35W	KB13260	74.5	6600	72.6
Kanby T5 Polycarbonate Controller SMART - 2x49W	KB13279	105.5	8600	64.4
Kanby T5 Polycarbonate Controller SMART - 35W	KB13308	39	3300	73.6
Kanby T5 Polycarbonate Controller SMART - 49W	KB13395	53	4300	73.0
Kanby T5 Reflector - 1x28W	KB10832	31	2600	76.3
Kanby T5 Reflector - 1x35W	KB10834	38	3300	81.6
Kanby T5 Reflector - 1x49W	KB10838	53	4300	73.0
Kanby T5 Reflector - 1x80W	KB10840	86	6450	65.3
Kanby T5 Reflector - 2x28W	KB10833	61	5200	74.2
Kanby T5 Reflector - 2x35W	KB10835	76	6600	78.2
Kanby T5 Reflector - 2x49W	KB10839	106	8600	68.2
Kanby T5 Reflector - 2x80W	KB12026	171	12900	63.4
Kanby T5 Reflector SMART - 2x49W	KB13276	105.5	8600	68.5
Kanby T5 Reflector SMART - 2x80W	KB13277	167	12900	64.9
Kanby ZIP - 15W - Low Glare	KZ19003	19	2480	130.5
Kanby ZIP - 15W - Opal	KZ18995	19	2380	125.3
Kanby ZIP - 15W - SMART - Low Glare	KZ18987	19	2480	130.5
Kanby ZIP - 15W - SMART - Opal	KZ18979	19	2380	125.3
Kanby ZIP - 22W - Low Glare	KZ19004	25	3470	138.8
Kanby ZIP - 22W - Opal	KZ18996	25	3330	133.2
Kanby ZIP - 22W - SMART - Low Glare	KZ18988	25	3470	138.8
Kanby ZIP - 22W - SMART - Opal	KZ18980	25	3330	133.2
Kanby ZIP - 36W - Low Glare	KZ19005	41	5490	133.9
Kanby ZIP - 36W - Opal	KZ18997	41	5270	128.5
Kanby ZIP - 36W - SMART - Low Glare	KZ18989	41	5490	133.9
Kanby ZIP - 36W - SMART - Opal	KZ18981	41	5270	128.5
Kanby ZIP - 43W - Low Glare	KZ19006	49	6510	132.9
Kanby ZIP - 43W - Opal	KZ18998	49	6250	127.6
Kanby ZIP - 43W - SMART - Low Glare	KZ18990	49	6510	132.9
Kanby ZIP - 43W - SMART - Opal	KZ18982	49	6250	127.6
Kanby ZIP - 53W - Opal	KZ19009	61	7680	125.9
Kanby ZIP - 53W - SMART - Opal	KZ19007	61	7680	125.9
LEDBay - 116W - Recessed	LY14902	125	9990	79.9
LEDBay - 116W - Surfaced	LY14904	125	9990	79.9
LEDBay SMART - 110W - Recessed	LY14903	125	9990	79.9
LEDBay SMART - 110W - Surfaced	LY14905	125	9990	79.9
Light Line - 1x28W	LL13331	31	2600	79.7
Light Line - 1x28W SMART	LL13337	30.5	2600	81.0
Light Line - 1x35W	LL13333	38	3300	78.2
Light Line - 1x35W SMART	LL13339	39	3300	76.2
Light Line - 1x49W	LL13335	53	4300	67.3
Light Line - 1x49W SMART	LL13341	53	4300	67.3
Light Line - 2x28W	LL13332	61	5200	66.5
Light Line - 2x28w SMART	LL13338	60.5	5200	67.0
Light Line - 2x35W	LL13334	76	6600	67.7
Light Line - 2x35W SMART	LL13340	74.5	6600	69.1
Light Line - 2x49W	LL13336	106	8600	63.3
Light Line - 2x49W SMART	LL13342	105.5	8600	63.6
Light Line Continuous - 1x28W	LL13343	31	2600	79.7
Light Line Continuous - 1x28W SMART	LL13349	30.5	2600	81.0

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Light Line Continuous - 1x35W	LL13345	38	3300	78.2
Light Line Continuous - 1x35W SMART	LL13351	39	3300	76.2
Light Line Continuous - 1x49W	LL13347	53	4300	67.3
Light Line Continuous - 1x49W SMART	LL13353	53	4300	67.3
Light Line Continuous - 2x28W	LL13344	61	5200	66.5
Light Line Continuous - 2x28W SMART	LL13350	60.5	5200	67.0
Light Line Continuous - 2x35W	LL13346	76	6600	67.7
Light Line Continuous - 2x35W SMART	LL13352	74.5	6600	69.1
Light Line Continuous - 2x49W	LL13348	106	8600	63.3
Light Line Continuous - 2x49W SMART	LL13354	105.5	8600	63.6
Light Line Integra Continuous - 1x28W	LL14290	31	2600	79.7
Light Line Integra Continuous - 1x28W SMART	LL14302	30.5	2600	81.0
Light Line Integra Continuous - 1x35W	LL14292	38	3300	78.2
Light Line Integra Continuous - 1x35W SMART	LL14304	39	3300	76.2
Light Line Integra Continuous - 1x49W	LL14294	53	4300	67.3
Light Line Integra Continuous - 1x49W SMART	LL14306	53	4300	67.3
Light Line Integra Continuous - 2x28W	LL14291	61	5200	66.5
Light Line Integra Continuous - 2x28W SMART	LL14303	60.5	5200	67.0
Light Line Integra Continuous - 2x35W	LL14293	76	6600	67.7
Light Line Integra Continuous - 2x35W SMART	LL14305	74.5	6600	69.1
Light Line Integra Continuous - 2x49W	LL14295	106	8600	63.3
Light Line Integra Continuous - 2x49W SMART	LL14307	105.5	8600	63.6
Lighting Line Integra LED Continuous - 24W	LL17605	28	4015	143.4
Lighting Line Integra LED Continuous - 24W SMART	LL17604	28	4015	143.4
Lighting Line Integra LED Continuous - 31W	LL16154	35	5020	143.4
Lighting Line Integra LED Continuous - 31W SMART	LL16158	35	5020	143.4
Lighting Line Integra LED Continuous - 42W	LL16153	48	6485	135.1
Lighting Line Integra LED Continuous - 42W SMART	LL16157	48	6485	135.1
Lighting Line Integra LED Continuous - 49W	LL16152	54	7385	136.8
Lighting Line Integra LED Continuous - 49W SMART	LL16156	54	7385	136.8
Lighting Line LED - 24W	LL17601	28	4015	143.4
Lighting Line LED - 24W SMART	LL17600	28	4015	143.4
Lighting Line LED - 31W	LL16042	35	5020	143.4
Lighting Line LED - 31W SMART	LL16046	35	5020	143.4
Lighting Line LED - 42W	LL16041	48	6485	135.1
Lighting Line LED - 42W SMART	LL16045	48	6485	135.1
Lighting Line LED - 49W	LL16040	54	7385	136.8
Lighting Line LED - 49W SMART	LL16044	54	7385	136.8
Lighting Line LED Continuous - 24W	LL17603	28	4015	143.4
Lighting Line LED Continuous - 24W SMART	LL17602	28	4015	143.4
Lighting Line LED Continuous - 31W	LL16052	35	5020	143.4
Lighting Line LED Continuous - 31W SMART	LL16056	35	5020	143.4
Lighting Line LED Continuous - 42W	LL16051	48	6485	135.1
Lighting Line LED Continuous - 42W SMART	LL16055	48	6485	135.1
Lighting Line LED Continuous - 49W	LL16050	54	7385	136.8
Lighting Line LED Continuous - 49W SMART	LL16054	54	7385	136.8
Medica - 29W LED Downlight	SMD16376	31	2450	79.0
Medica - 29W LED Uplight	SMD16377	31	2450	79.0
Medica - 39W LED Downlight	SMD16378	44	3265	74.2
Medica - 39W LED Uplight	SMD16378	44	3265	74.2
Mercian LED - 26W 4000K	MER19104	30	3330	111.0
Mercian LED - 26W 5700K	MER19105	30	3330	111.0
Mercian LED SMART - 26W 4000K	MER19102	30	3330	111.0

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Mercian LED SMART - 26W 5700K	MER19103	30	3330	111.0
Microdot - 13W LED	MID16449	14	1145	81.8
Mina-L 17° Beam - 20W - 3000K	MA17970	24	2170	90.4
Mina-L 17° Beam - 20W - 4000K	MA17974	24	2335	97.3
Mina-L 17° Beam - 28W - 3000K	MA17971	35	2720	77.7
Mina-L 17° Beam - 28W - 4000K	MA17975	35	2925	83.6
Mina-L 17° Beam - 35W - 3000K	MA17972	41	3370	82.2
Mina-L 17° Beam - 35W - 4000K	MA17976	41	3625	88.4
Mina-L 28° Beam - 20W - 3000K	MA17978	24	1980	82.5
Mina-L 28° Beam - 20W - 4000K	MA17982	24	2130	88.8
Mina-L 28° Beam - 28W - 3000K	MA17979	35	2485	71.0
Mina-L 28° Beam - 28W - 4000K	MA17983	35	2670	76.3
Mina-L 28° Beam - 35W - 3000K	MA17980	41	3075	75.0
Mina-L 28° Beam - 35W - 4000K	MA17984	41	3305	80.6
Mina-L 41° Beam - 20W - 3000K	MA17986	24	1960	81.7
Mina-L 41° Beam - 20W - 4000K	MA17990	24	2110	87.9
Mina-L 41° Beam - 28W - 3000K	MA17987	35	2460	70.3
Mina-L 41° Beam - 28W - 4000K	MA17991	35	2645	75.6
Mina-L 41° Beam - 35W - 3000K	MA17988	41	3045	74.3
Mina-L 41° Beam - 35W - 4000K	MA17992	41	3275	79.9
Mina-M 30° Beam - 14W - 3000K - Round Version	MA17950	17	1445	85.0
Mina-M 30° Beam - 14W - 3000K - Square Version	MA17958	17	1445	85.0
Mina-M 30° Beam - 14W - 4000K - Round Version	MA17952	17	1555	91.5
Mina-M 30° Beam - 14W - 4000K - Square Version	MA17960	17	1555	91.5
Mina-M 30° Beam - 20W - 3000K - Round Version	MA17951	24	1980	82.5
Mina-M 30° Beam - 20W - 3000K - Square Version	MA17959	24	1980	82.5
Mina-M 30° Beam - 20W - 4000K - Round Version	MA17953	24	2130	88.8
Mina-M 30° Beam - 20W - 4000K - Square Version	MA17961	24	2130	88.8
Mina-M 38° Beam - 14W - 3000K - Round Version	MA17954	17	1430	84.1
Mina-M 38° Beam - 14W - 3000K - Square Version	MA17962	17	1430	84.1
Mina-M 38° Beam - 14W - 4000K - Round Version	MA17956	17	1540	90.6
Mina-M 38° Beam - 14W - 4000K - Square Version	MA17964	17	1540	90.6
Mina-M 38° Beam - 20W - 3000K - Round Version	MA17955	24	1960	81.7
Mina-M 38° Beam - 20W - 3000K - Square Version	MA17963	24	1960	81.7
Mina-M 38° Beam - 20W - 4000K - Round Version	MA17957	24	2110	87.9
Mina-M 38° Beam - 20W - 4000K - Square Version	MA17965	24	2110	87.9
Mina-S 21° Beam - 5W - 3000K - Round Version	MA17930	6	490	81.7
Mina-S 21° Beam - 5W - 3000K - Square Version	MA17938	6	490	81.7
Mina-S 21° Beam - 5W - 4000K - Round Version	MA17932	6	525	87.5
Mina-S 21° Beam - 5W - 4000K - Square Version	MA17940	6	525	87.5
Mina-S 21° Beam - 8W - 3000K - Round Version	MA17931	9	720	80.0
Mina-S 21° Beam - 8W - 3000K - Square Version	MA17939	9	720	80.0
Mina-S 21° Beam - 8W - 4000K - Round Version	MA17933	9	775	86.1
Mina-S 21° Beam - 8W - 4000K - Square Version	MA17941	9	775	86.1
Mina-S 45° Beam - 5W - 3000K - Round Version	MA17934	6	455	75.8
Mina-S 45° Beam - 5W - 3000K - Square Version	MA17942	6	455	75.8
Mina-S 45° Beam - 5W - 4000K - Round Version	MA17936	6	490	81.7
Mina-S 45° Beam - 5W - 4000K - Square Version	MA17944	6	490	81.7
Mina-S 45° Beam - 8W - 3000K - Round Version	MA17935	9	675	75.0
Mina-S 45° Beam - 8W - 3000K - Square Version	MA17943	9	675	75.0
Mina-S 45° Beam - 8W - 4000K - Round Version	MA17937	9	725	80.6
Mina-S 45° Beam - 8W - 4000K - Square Version	MA17945	9	725	80.6
Nemus - 17W - 3000K	NEM18028	20	2015	100.8

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Nemus - 17W - 4000K	NEM18030	20	2165	108.3
Nemus - 26W - 3000K	NEM18029	30	2870	95.7
Nemus - 26W - 4000K	NEM18031	30	3085	102.8
Ovix LED - 10W - 4000K	OV19286	13	1665	128.1
Ovix LED - 10W- SMART - 4000K	OV19280	13	1665	128.1
Ovix LED - 17W - 4000K	OV19284	19	2705	142.4
Ovix LED - 17W- SMART - 4000K	OV19281	19	2705	142.4
Ovix LED - 24W - 4000K	OV19285	27	3685	136.5
Ovix LED - 24W- SMART - 4000K	OV19282	27	3685	136.5
Passlight Glass - 26W	PL11922	47	1800	23.7
Passlight Glass - 32W	PL11922	47	2400	31.7
Passlight Glass - 42W	PL11922	47	3200	42.2
Passlight Glass - 57W	PL11923	62	4300	43.0
Passlight Glass - 70W	PL6235	86	5600	41.7
Passlight LED Glass Cover - 24W	PL14898	27	2535	93.9
Passlight LED Glass Cover - 38W	PL14900	40	3440	86.0
Passlight LED Polycarbonate Cover - 24W	PL14897	27	2335	86.5
Passlight LED Polycarbonate Cover - 38W	PL14899	40	3165	79.1
Passlight Polycarbonate - 26W	PL11932	47	1800	21.4
Passlight Polycarbonate - 32W	PL11932	47	2400	28.6
Passlight Polycarbonate - 42W	PL11932	47	3200	38.1
Passlight Polycarbonate - 57W	PL11933	62	4300	38.8
Passlight Polycarbonate - 70W	PL6281	86	5600	38.4
Passway 11W Area 1100mm Root Mounted	PW19912	14	875	62.5
Passway 11W Area 1100mm Surface Mounted	PW19910	14	875	62.5
Passway 11W Area 850mm Root Mounted	PW19917	14	875	62.5
Passway 11W Area 850mm Surface Mounted	PW19914	14	875	62.5
Passway 11W Pathway 1100mm Root Mounted	PW19913	14	780	55.7
Passway 11W Pathway 1100mm Surface Mounted	PW19911	14	780	55.7
Passway 11W Pathway 850mm Root Mounted	PW19918	14	780	55.7
Passway 11W Pathway 850mm Surface Mounted	PW19915	14	780	55.7
Passway 21W Area 1100mm Root Mounted	PW19913	25	1495	59.8
Passway 21W Area 1100mm Surface Mounted	PW19911	25	1495	59.8
Passway 21W Area 850mm Root Mounted	PW19918	25	1495	59.8
Passway 21W Area 850mm Surface Mounted	PW19915	25	1495	59.8
Passway 5W Pathway 1100mm Root Mounted	PW19912	9	450	50.0
Passway 5W Pathway 1100mm Surface Mounted	PW19910	9	450	50.0
Passway 5W Pathway 850mm Root Mounted	PW19917	9	450	50.0
Passway 5W Pathway 850mm Surface Mounted	PW19914	9	450	50.0
Pitch-L 17° Beam - 14W - 3000K	PTC18120	18	1455	80.8
Pitch-L 17° Beam - 14W - 4000K	PTC18124	18	1565	86.9
Pitch-L 17° Beam - 20W - 3000K	PTC18121	24	2170	90.4
Pitch-L 17° Beam - 20W - 4000K	PTC18125	24	2335	97.3
Pitch-L 17° Beam - 28W - 3000K	PTC18122	35	2720	77.7
Pitch-L 17° Beam - 28W - 4000K	PTC18126	35	2925	83.6
Pitch-L 17° Beam - 35W - 3000K	PTC18123	41	3370	82.2
Pitch-L 17° Beam - 35W - 4000K	PTC18127	41	3625	88.4
Pitch-L 28° Beam - 14W - 3000K	PTC18128	18	1330	73.9
Pitch-L 28° Beam - 14W - 4000K	PTC18132	18	1430	79.4
Pitch-L 28° Beam - 20W - 3000K	PTC18129	24	1980	82.5
Pitch-L 28° Beam - 20W - 4000K	PTC18133	24	2130	88.8
Pitch-L 28° Beam - 28W - 3000K	PTC18130	35	2485	71.0
Pitch-L 28° Beam - 28W - 4000K	PTC18134	35	2670	76.3



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Pitch-L 28° Beam - 35W - 3000K	PTC18131	41	3075	75.0
Pitch-L 28° Beam - 35W - 4000K	PTC18135	41	3305	80.6
Pitch-L 41° Beam - 14W - 3000K	PTC18136	18	1410	78.3
Pitch-L 41° Beam - 14W - 4000K	PTC18140	18	1515	84.2
Pitch-L 41° Beam - 20W - 3000K	PTC18137	24	1960	81.7
Pitch-L 41° Beam - 20W - 4000K	PTC18141	24	2110	87.9
Pitch-L 41° Beam - 28W - 3000K	PTC18138	35	2460	70.3
Pitch-L 41° Beam - 28W - 4000K	PTC18142	35	2645	75.6
Pitch-L 41° Beam - 35W - 3000K	PTC18139	41	3045	74.3
Pitch-L 41° Beam - 35W - 4000K	PTC18143	41	3275	79.9
Pitch-M 19° Beam - 14W - 3000K	PTC18101	17	1385	81.5
Pitch-M 19° Beam - 14W - 4000K	PTC18104	17	1490	87.6
Pitch-M 19° Beam - 20W - 3000K	PTC18102	24	1895	79.0
Pitch-M 19° Beam - 20W - 4000K	PTC18105	24	2040	85.0
Pitch-M 19° Beam - 6W - 3000K	PTC18100	8	640	80.0
Pitch-M 19° Beam - 6W - 4000K	PTC18103	8	690	86.3
Pitch-M 30° Beam - 14W - 3000K	PTC18107	17	1445	85.0
Pitch-M 30° Beam - 14W - 4000K	PTC18110	17	1555	91.5
Pitch-M 30° Beam - 20W - 3000K	PTC18108	24	1980	82.5
Pitch-M 30° Beam - 20W - 4000K	PTC18111	24	2130	88.8
Pitch-M 30° Beam - 6W - 3000K	PTC18106	8	670	83.8
Pitch-M 30° Beam - 6W - 4000K	PTC18109	8	720	90.0
Pitch-M 38° Beam - 14W - 3000K	PTC18113	17	1430	84.1
Pitch-M 38° Beam - 14W - 4000K	PTC18116	17	1540	90.6
Pitch-M 38° Beam - 20W - 3000K	PTC18114	24	1960	81.7
Pitch-M 38° Beam - 20W - 4000K	PTC18117	24	2110	87.9
Pitch-M 38° Beam - 6W - 3000K	PTC18112	8	665	83.1
Pitch-M 38° Beam - 6W - 4000K	PTC18115	8	715	89.4
Pitlight - Glass - 2x40W	PG12821	89	7000	43.3
Pitlight - Polycarbonate - 2x40W	PG11903	89	7000	43.3
Pivitz 17° Beam - 14W - 3000K - With Barn Door	PIV18170	18	1455	80.8
Pivitz 17° Beam - 14W - 3000K - Without Barn Door	PIV18150	18	1455	80.8
Pivitz 17° Beam - 14W - 4000K - With Barn Door	PIV18173	18	1565	86.9
Pivitz 17° Beam - 14W - 4000K - Without Barn Door	PIV18153	18	1565	86.9
Pivitz 17° Beam - 20W - 3000K - With Barn Door	PIV18171	24	2170	90.4
Pivitz 17° Beam - 20W - 3000K - Without Barn Door	PIV18151	24	2170	90.4
Pivitz 17° Beam - 20W - 4000K - With Barn Door	PIV18174	24	2335	97.3
Pivitz 17° Beam - 20W - 4000K - Without Barn Door	PIV18154	24	2335	97.3
Pivitz 17° Beam - 28W - 3000K - With Barn Door	PIV18172	35	2720	77.7
Pivitz 17° Beam - 28W - 3000K - Without Barn Door	PIV18152	35	2720	77.7
Pivitz 17° Beam - 28W - 4000K - With Barn Door	PIV18175	35	2925	83.6
Pivitz 17° Beam - 28W - 4000K - Without Barn Door	PIV18155	35	2925	83.6
Pivitz 28° Beam - 14W - 3000K - With Barn Door	PIV18176	18	1330	73.9
Pivitz 28° Beam - 14W - 3000K - Without Barn Door	PIV18156	18	1330	73.9
Pivitz 28° Beam - 14W - 4000K - With Barn Door	PIV18179	18	1430	79.4
Pivitz 28° Beam - 14W - 4000K - Without Barn Door	PIV18159	18	1430	79.4
Pivitz 28° Beam - 20W - 3000K - With Barn Door	PIV18177	24	1980	82.5
Pivitz 28° Beam - 20W - 3000K - Without Barn Door	PIV18157	24	1980	82.5
Pivitz 28° Beam - 20W - 4000K - With Barn Door	PIV18180	24	2130	88.8
Pivitz 28° Beam - 20W - 4000K - Without Barn Door	PIV18160	24	2130	88.8
Pivitz 28° Beam - 28W - 3000K - With Barn Door	PIV18178	35	2485	71.0
Pivitz 28° Beam - 28W - 3000K - Without Barn Door	PIV18158	35	2485	71.0
Pivitz 28° Beam - 28W - 4000K - With Barn Door	PIV18181	35	2670	76.3

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Pivitz 28° Beam - 28W - 4000K - Without Barn Door	PIV18161	35	2670	76.3
Pivitz 41° Beam - 14W - 3000K - With Barn Door	PIV18182	18	1410	78.3
Pivitz 41° Beam - 14W - 3000K - Without Barn Door	PIV18162	18	1410	78.3
Pivitz 41° Beam - 14W - 4000K - With Barn Door	PIV18185	18	1515	84.2
Pivitz 41° Beam - 14W - 4000K - Without Barn Door	PIV18165	18	1515	84.2
Pivitz 41° Beam - 20W - 3000K - With Barn Door	PIV18183	24	1960	81.7
Pivitz 41° Beam - 20W - 3000K - Without Barn Door	PIV18163	24	1960	81.7
Pivitz 41° Beam - 20W - 4000K - With Barn Door	PIV18186	24	2110	87.9
Pivitz 41° Beam - 20W - 4000K - Without Barn Door	PIV18166	24	2110	87.9
Pivitz 41° Beam - 28W - 3000K - With Barn Door	PIV18184	35	2460	70.3
Pivitz 41° Beam - 28W - 3000K - Without Barn Door	PIV18164	35	2460	70.3
Pivitz 41° Beam - 28W - 4000K - With Barn Door	PIV18187	35	2645	75.6
Pivitz 41° Beam - 28W - 4000K - Without Barn Door	PIV18167	35	2645	75.6
Plateau LED - 16W - ColourControl	PU18002CC	17	1900	111.8
Plateau LED - 16W - SMART - ColourActive	PU18809CA	17	1900	111.8
Plateau LED - 31W - ColourControl	PU18003CC	34	3795	111.6
Plateau LED - 31W - SMART - ColourActive	PU18810CA	34	3795	111.6
Plateau LED - 41W - ColourControl	PU19137CC	47	5475	116.5
Plateau LED - 41W - SMART - ColourActive	PU19136CA	47	5475	116.5
Plateau LED 4000K - 20W	PU17592	23	2850	123.9
Plateau LED 4000K - 26W	PU16528	30	3570	119.0
Plateau LED 4000K - 38W	PU16529	43	4885	113.6
Plateau LED 4000K SMART - 20W	PU17590	23	2850	123.9
Plateau LED 4000K SMART - 26W	PU16526	30	3570	119.0
Plateau LED 4000K SMART - 38W	PU16527	43	4885	113.6
Plateau LED 6500K - 20W	PU17593	23	2850	123.9
Plateau LED 6500K - 26W	PU16544	30	3570	119.0
Plateau LED 6500K - 38W	PU16545	43	4885	113.6
Plateau LED 6500K SMART - 20W	PU17591	23	2850	123.9
Plateau LED 6500K SMART - 26W	PU16542	30	3570	119.0
Plateau LED 6500K SMART - 38W	PU16543	43	4885	113.6
Prismalette LED Clear Cover - 11W	PS17608	14	1500	107.1
Prismalette LED Clear Cover - 16W	PS14913	19	2280	120.0
Prismalette LED Low Profile Satin Cover - 11W	PS18420	14	1605	114.6
Prismalette LED Low Profile Satin Cover - 16W	PS18421	19	2170	114.2
Prismalette LED Satin Cover - 11W	PS17609	14	1410	100.7
Prismalette LED Satin Cover - 16W	PS14914	19	2145	112.9
Prismalette Pro LED Ceiling Mounted - 16W	PS17313	19	1815	95.5
Prismalette Pro LED Wall Mounted - 12W	PS17312	15	1370	91.3
Prismalux Glass - 26W	PX11921	47	1800	28.0
Prismalux Glass - 32W	PX11921	47	2400	37.3
Prismalux Glass - 42W	PX11921	47	3200	49.7
Prismalux Glass - 50W SON-E	PX6537	65	3500	39.3
Prismalux Glass - 70W	PX5235	86	5600	47.5
Prismalux LED Glass Cover - 20W	PX14933	24	2640	110.0
Prismalux LED Glass Cover - 32W	PX14935	34	4255	125.1
Prismalux LED Polycarbonate Cover - 20W	PX14932	24	2455	102.3
Prismalux LED Polycarbonate Cover - 32W	PX14934	34	4010	117.9
Prismalux LED Zone 2 & 22 - 25W	PX17483	26	2795	107.5
Prismalux Polycarbonate - 26W	PX11931	47	1800	26.4
Prismalux Polycarbonate - 32W	PX11931	47	2400	35.2
Prismalux Polycarbonate - 42W	PX11931	47	3200	47.0
Prismalux Polycarbonate - 50W SON-E	PX6539	65	3500	37.2

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Prismalux Polycarbonate - 70W	PX6385	86	5300	42.5
Quadline - 19W - 3000K	QL18056	23	1895	82.4
Quadline - 19W - 4000K	QL18058	23	2040	88.7
Quadline - 38W - 3000K	QL18057	44	3795	86.3
Quadline - 38W - 4000K	QL18059	44	4080	92.7
Quadrum - 17W - 3000K	QR18050	20	1875	93.8
Quadrum - 17W - 4000K	QR18053	20	2015	100.8
Quadrum - 26W - 3000K	QR18051	30	2665	88.8
Quadrum - 26W - 4000K	QR18054	30	2865	95.5
Quadrum - 41W - 3000K	QR18052	47	3745	79.7
Quadrum - 41W - 4000K	QR18055	47	4025	85.6
R3 LED Low Glare - 18W - 3000K	RT18221	22	1595	72.5
R3 LED Low Glare - 18W - 4000K	RT18223	22	1695	77.0
R3 LED Low Glare - 9W - 3000K	RT18220	10	845	84.5
R3 LED Low Glare - 9W - 4000K	RT18222	10	900	90.0
R3 LED Low Glare SMART - 18W - 3000K	RT18217	22	1595	72.5
R3 LED Low Glare SMART - 18W - 4000K	RT18219	22	1695	77.0
R3 LED Low Glare SMART - 9W - 3000K	RT18216	10	845	84.5
R3 LED Low Glare SMART - 9W - 4000K	RT18218	10	900	90.0
R3 LED Opal - 18W - 3000K	RT18205	22	1755	79.8
R3 LED Opal - 18W - 4000K	RT18207	22	1865	84.8
R3 LED Opal - 9W - 3000K	RT18204	10	950	95.0
R3 LED Opal - 9W - 4000K	RT18206	10	1010	101.0
R3 LED Opal Halo - 18W - 3000K	RT18213	22	1700	77.3
R3 LED Opal Halo - 18W - 4000K	RT18215	22	1810	82.3
R3 LED Opal Halo - 9W - 4000K	RT18214	10	985	98.5
R3 LED Opal Halo - 9W - 3000K	RT18212	10	925	92.5
R3 LED Opal Halo SMART - 18W - 3000K	RT18209	22	1700	77.3
R3 LED Opal Halo SMART - 18W - 4000K	RT18211	22	1810	82.3
R3 LED Opal Halo SMART - 9W - 3000K	RT18208	10	925	92.5
R3 LED Opal Halo SMART - 9W - 4000K	RT18210	10	985	98.5
R3 LED Opal SMART - 18W - 3000K	RT18201	22	1755	79.8
R3 LED Opal SMART - 18W - 4000K	RT18203	22	1865	84.8
R3 LED Opal SMART - 9W - 3000K	RT18200	10	950	95.0
R3 LED Opal SMART - 9W - 4000K	RT18202	10	1010	101.0
R4 LED Low Glare - 18W - 3000K	RF18247	22	1785	81.1
R4 LED Low Glare - 18W - 4000K	RF18249	22	1900	86.4
R4 LED Low Glare - 9W - 3000K	RF18246	10	900	90.0
R4 LED Low Glare - 9W - 4000K	RF18248	10	955	95.5
R4 LED Low Glare SMART - 18W - 3000K	RF18243	22	1785	81.1
R4 LED Low Glare SMART - 18W - 4000K	RF18245	22	1900	86.4
R4 LED Low Glare SMART - 9W - 3000K	RF18242	10	900	90.0
R4 LED Low Glare SMART - 9W - 4000K	RF18244	10	955	95.5
R4 LED Opal - 18W - 3000K	RF18231	22	1970	89.5
R4 LED Opal - 18W - 4000K	RF18233	22	2095	95.2
R4 LED Opal - 9W - 3000K	RF18230	10	980	98.0
R4 LED Opal - 9W - 4000K	RF18232	10	1040	104.0
R4 LED Opal Halo - 18W - 3000K	RF18239	22	1915	87.0
R4 LED Opal Halo - 18W - 4000K	RF18241	22	2035	92.5
R4 LED Opal Halo - 9W - 4000K	RF18240	10	1020	102.0
R4 LED Opal Halo - 9W - 3000K	RF18238	10	960	96.0
R4 LED Opal Halo SMART - 18W - 3000K	RF18235	22	1915	87.0
R4 LED Opal Halo SMART - 18W - 4000K	RF18237	22	2035	92.5

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
R4 LED Opal Halo SMART - 9W - 3000K	RF18234	10	960	96.0
R4 LED Opal Halo SMART - 9W - 4000K	RF18236	10	1020	102.0
R4 LED Opal SMART - 18W - 3000K	RF18227	22	1970	89.5
R4 LED Opal SMART - 18W - 4000K	RF18229	22	2095	95.2
R4 LED Opal SMART - 9W - 3000K	RF18226	10	980	98.0
R4 LED Opal SMART - 9W - 4000K	RF18228	10	1040	104.0
Radiance - 16W	RAD16404	18	2335	129.7
Radiance - 28W	RAD16405	31	4130	133.2
Radiance - 38W	RAD16406	41	5375	131.1
Radiance - 51W	RAD16407	59	7650	129.7
Radiance 1200 x 300 - 16W	RAD16717	18	2255	125.3
Radiance 1200 x 300 - 28W	RAD16718	31	4010	129.4
Radiance 1200 x 300 - 38W	RAD16719	41	5180	126.3
Radiance 1200 x 300 - 51W	RAD16720	59	7315	124.0
Radiance Corridor LED 24W	RC18820	26	2980	114.6
Radiance Corridor LED 24W - SMART	RC18819	26	2980	114.6
Radiance LG7 - 16W	RAD16725	18	2085	115.8
Radiance LG7 - 28W	RAD16726	31	3715	119.8
Radiance LG7 - 38W	RAD16727	41	4770	116.3
Radiance LG7 - 51W	RAD16728	59	6695	113.5
Radiance LG7 SMART - 16W	RAD16721	18	2085	115.8
Radiance LG7 SMART - 28W	RAD16722	31	3715	119.8
Radiance LG7 SMART - 38W	RAD16723	41	4770	116.3
Radiance LG7 SMART - 51W	RAD16724	59	6695	113.5
Radiance LG7 Surface - 16W	RAD16932	18	2085	115.8
Radiance LG7 Surface - 28W	RAD16933	31	3715	119.8
Radiance LG7 Surface - 38W	RAD16934	41	4770	116.3
Radiance LG7 Surface - 51W	RAD16935	59	6695	113.5
Radiance LG7 Surface SMART - 16W	RAD16928	18	2085	115.8
Radiance LG7 Surface SMART - 28W	RAD16929	31	3715	119.8
Radiance LG7 Surface SMART - 38W	RAD16930	41	4770	116.3
Radiance LG7 Surface SMART - 51W	RAD16931	59	6695	113.5
Radiance SMART - 16W	RAD16400	18	2335	129.7
Radiance SMART - 28W	RAD16401	31	4130	133.2
Radiance SMART - 38W	RAD16402	41	5375	131.1
Radiance SMART - 51W	RAD16403	59	7650	129.7
Radiance SMART 1200 x 300 - 16W	RAD16713	18	2255	125.3
Radiance SMART 1200 x 300 - 28W	RAD16714	31	4010	129.4
Radiance SMART 1200 x 300 - 38W	RAD16715	41	5180	126.3
Radiance SMART 1200 x 300 - 51W	RAD16716	59	7315	124.0
Radiance Surface - 16W	RAD16924	18	2335	129.7
Radiance Surface - 28W	RAD16925	31	4130	133.2
Radiance Surface - 38W	RAD16926	41	5375	131.1
Radiance Surface - 51W	RAD16927	59	7650	129.7
Radiance Surface 1200 x 300 - 51W	RAD17061	59	7315	124.0
Radiance Surface 1200 x 300 - 16W	RAD17058	18	2255	125.3
Radiance Surface 1200 x 300 - 28W	RAD17059	31	4010	129.4
Radiance Surface 1200 x 300 - 38W	RAD17060	41	5180	126.3
Radiance Surface SMART - 16W	RAD16920	18	2255	125.3
Radiance Surface SMART - 28W	RAD16921	31	4010	129.4
Radiance Surface SMART - 38W	RAD16922	41	5180	126.3
Radiance Surface SMART - 51W	RAD16923	59	7315	124.0
Radiance Surface SMART 1200 x 300 - 51W	RAD17057	59	7315	124.0

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Radiance Surface SMART 1200 x 300 - 16W	RAD17054	18	2255	125.3
Radiance Surface SMART 1200 x 300 - 28W	RAD17055	31	4010	129.4
Radiance Surface SMART 1200 x 300 - 38W	RAD17056	41	5180	126.3
Radiance Suspended - 16W	RAD17009	18	2335	129.7
Radiance Suspended - 28W	RAD17010	31	4130	133.2
Radiance Suspended - 38W	RAD17011	41	5375	131.1
Radiance Suspended - 51W	RAD17012	59	7650	129.7
Radiance Suspended SMART - 16W	RAD17005	18	2335	129.7
Radiance Suspended SMART - 28W	RAD17006	31	4130	133.2
Radiance Suspended SMART - 38W	RAD17007	41	5375	131.1
Radiance Suspended SMART - 51W	RAD17008	59	7650	129.7
Realta LED - 20W - Area Distribution - Polycarbonate Cover - 4000K	RL19116	23	2840	123.5
Realta LED - 20W - Area Distribution - Polycarbonate Cover - 4000K - Ligature Resistant	RL19116T	23	2840	123.5
Realta LED - 20W - Area Distribution - Polycarbonate Cover - 5700K	RL19119	23	2840	123.5
Realta LED - 20W - Area Distribution - Polycarbonate Cover - 5700K - Ligature Resistant	RL19119T	23	2840	123.5
Realta LED - 20W - SMART - Area Distribution - Polycarbonate Cover - 4000K	RL19110	23	2840	123.5
Realta LED - 20W - SMART - Area Distribution - Polycarbonate Cover - 5700K	RL19113	23	2840	123.5
Realta LED - 34W - Area Distribution - Polycarbonate Cover - 4000K	RL19117	38	4850	127.6
Realta LED - 34W - Area Distribution - Polycarbonate Cover - 4000K - Ligature Resistant	RL19117T	38	4850	127.6
Realta LED - 34W - Area Distribution - Polycarbonate Cover - 5700K	RL19120	38	4850	127.6
Realta LED - 34W - Area Distribution - Polycarbonate Cover - 5700K - Ligature Resistant	RL19120T	38	4850	127.6
Realta LED - 34W - SMART - Area Distribution - Polycarbonate Cover - 4000K	RL19111	38	4850	127.6
Realta LED - 34W - SMART - Area Distribution - Polycarbonate Cover - 5700K	RL19114	38	4850	127.6
Realta LED - 42W - Area Distribution - Polycarbonate Cover - 4000K	RL19118	47	5635	119.9
Realta LED - 42W - Area Distribution - Polycarbonate Cover - 4000K - Ligature Resistant	RL19118T	47	5635	119.9
Realta LED - 42W - Area Distribution - Polycarbonate Cover - 5700K	RL19121	47	5635	119.9
Realta LED - 42W - Area Distribution - Polycarbonate Cover - 5700K - Ligature Resistant	RL19121T	47	5635	119.9
Realta LED - 42W - SMART - Area Distribution - Polycarbonate Cover - 4000K	RL19112	47	5635	119.9
Realta LED - 42W - SMART - Area Distribution - Polycarbonate Cover - 5700K	RL19115	47	5635	119.9
Realta LED - 8W - SMART - Wide Distribution - Polycarbonate Cover - 4000K	RL19069	11	1320	120.0
Realta LED - 8W - SMART - Wide Distribution - Polycarbonate Cover - 5700K	RL19070	11	1320	120.0
Realta LED - 8W - Wide Distribution - Glass Cover - 4000K	RL19073	11	1175	106.8
Realta LED - 8W - Wide Distribution - Glass Cover - 4000K - Ligature Resistant	RL19073T	11	1175	106.8
Realta LED - 8W - Wide Distribution - Glass Cover - 5700K	RL19074	11	1175	106.8
Realta LED - 8W - Wide Distribution - Glass Cover - 5700K - Ligature Resistant	RL19074T	11	1175	106.8
Realta LED - 8W - Wide Distribution - Polycarbonate Cover - 4000K	RL19071	11	1320	120.0
Realta LED - 8W - Wide Distribution - Polycarbonate Cover - 4000K - Ligature Resistant	RL19071T	11	1320	120.0
Realta LED - 8W - Wide Distribution - Polycarbonate Cover - 5700K	RL19072	11	1320	120.0
Realta LED - 8W - Wide Distribution - Polycarbonate Cover - 5700K - Ligature Resistant	RL19072T	11	1320	120.0
Realta Micro LED - 3W	RL13543	3	80	26.7
Realta Micro LED - 6W	RL16607	8	519	64.9
Sky-Dome LED - 16W - ColourControl	SD17247CC	17	1975	116.2
Sky-Dome LED - 16W - SMART - ColourActive	SD18807CA	17	1975	116.2
Sky-Dome LED - 31W - ColourControl	SD17248CC	34	3865	113.7
Sky-Dome LED - 31W - SMART - ColourActive	SD18808CA	34	3865	113.7
Sky-Dome LED - 41W - ColourControl	SD19139CC	47	5575	118.6
Sky-Dome LED - 41W - SMART - ColourActive	SD19138CA	47	5575	118.6
Sky-Dome LED 4000K - 20W	SD17627	23	2490	108.3

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Sky-Dome LED 4000K - 26W	SD16532	30	3445	114.8
Sky-Dome LED 4000K - 38W	SD16533	44	4865	110.6
Sky-Dome LED 4000K - 74W	SD17629	84	8540	101.7
Sky-Dome LED 4000K SMART - 20W	SD17623	23	2490	108.3
Sky-Dome LED 4000K SMART - 26W	SD16530	30	3445	114.8
Sky-Dome LED 4000K SMART - 74W	SD17625	84	8540	101.7
Sky-Dome LED 4000K SMART - 38W	SD16531	44	4865	110.6
Sky-Dome LED 6500K - 20W	SD17628	23	2490	108.3
Sky-Dome LED 6500K - 26W	SD16548	30	3445	114.8
Sky-Dome LED 6500K - 38W	SD16549	44	4865	110.6
Sky-Dome LED 6500K - 74W	SD17630	84	8540	101.7
Sky-Dome LED 6500K SMART - 20W	SD16546	30	3445	114.8
Sky-Dome LED 6500K SMART - 26W	SD17624	23	2490	108.3
Sky-Dome LED 6500K SMART - 74W	SD17626	84	8540	101.7
Sky-Dome LED 6500K SMART - 38W	SD16547	44	4865	110.6
Solis-L 17° Beam - 17W - 3000K	SOL17832	24	2170	90.4
Solis-L 17° Beam - 17W - 4000K	SOL17836	24	2335	97.3
Solis-L 17° Beam - 28W - 3000K	SOL17833	35	2720	77.7
Solis-L 17° Beam - 28W - 4000K	SOL17837	35	2925	83.6
Solis-L 17° Beam - 35W - 3000K	SOL17834	41	3370	82.2
Solis-L 17° Beam - 35W - 4000K	SOL17838	41	3625	88.4
Solis-L 28° Beam - 17W - 3000K	SOL17840	24	1980	82.5
Solis-L 28° Beam - 17W - 4000K	SOL17844	24	2130	88.8
Solis-L 28° Beam - 28W - 3000K	SOL17841	35	2485	71.0
Solis-L 28° Beam - 28W - 4000K	SOL17845	35	2670	76.3
Solis-L 28° Beam - 35W - 3000K	SOL17842	41	3075	75.0
Solis-L 28° Beam - 35W - 4000K	SOL17846	41	3305	80.6
Solis-L 41° Beam - 17W - 3000K	SOL17848	24	1960	81.7
Solis-L 41° Beam - 17W - 4000K	SOL17852	24	2110	87.9
Solis-L 41° Beam - 28W - 3000K	SOL17849	35	2460	70.3
Solis-L 41° Beam - 28W - 4000K	SOL17853	35	2645	75.6
Solis-L 41° Beam - 35W - 3000K	SOL17850	41	3045	74.3
Solis-L 41° Beam - 35W - 4000K	SOL17854	41	3275	79.9
Solis-M 30° Beam - 14W - 3000K	SOL17800	17	1445	85.0
Solis-M 30° Beam - 14W - 4000K	SOL17802	17	1555	91.5
Solis-M 30° Beam - 20W - 3000K	SOL17801	24	1980	82.5
Solis-M 30° Beam - 20W - 4000K	SOL17803	24	2130	88.8
Solis-M 38° Beam - 14W - 3000K	SOL17804	17	1430	84.1
Solis-M 38° Beam - 14W - 4000K	SOL17806	17	1540	90.6
Solis-M 38° Beam - 20W - 3000K	SOL17805	24	1960	81.7
Solis-M 38° Beam - 20W - 4000K	SOL17807	24	2110	87.9
Solow LED Broad - 126W	SWL17375	132	17825	135.0
Solow LED Broad - 189W	SWL17376	200	26740	133.7
Solow LED Broad - 252W	SWL17377	265	35650	134.5
Solow LED Broad HL SMART - 126W	SWL17369	132	17825	135.0
Solow LED Broad HL SMART - 189W	SWL17370	200	26740	133.7
Solow LED Broad HL SMART - 252W	SWL17371	265	35650	134.5
Solow LED Broad SMART - 126W	SWL17363	132	17825	135.0
Solow LED Broad SMART - 189W	SWL17364	200	26740	133.7
Solow LED Broad SMART - 252W	SWL17365	265	35650	134.5
Solow LED Narrow - 126W	SWL17378	132	17665	133.8
Solow LED Narrow - 189W	SWL17379	200	26500	132.5
Solow LED Narrow - 252W	SWL17380	265	35330	133.3

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Solow LED Narrow HL SMART - 126W	SWL17372	132	17665	133.8
Solow LED Narrow HL SMART - 189W	SWL17373	200	26500	132.5
Solow LED Narrow HL SMART - 252W	SWL17374	265	35330	133.3
Solow LED Narrow SMART - 126W	SWL17366	132	17665	133.8
Solow LED Narrow SMART - 189W	SWL17367	200	26500	132.5
Solow LED Narrow SMART - 252W	SWL17368	265	35330	133.3
Solow XLED Broad - 112W	SWX19042	119	17965	151.0
Solow XLED Broad - 175W	SWX19043	188	25870	137.6
Solow XLED Broad - 190W	SWX16992	205	30785	150.2
Solow XLED Broad - 215W	SWX19044	229	37100	162.0
Solow XLED Broad - 65W	SWX16990	68	10585	155.7
Solow XLED Broad SMART - 112W	SWX19036	119	17965	151.0
Solow XLED Broad SMART - 175W	SWX19037	188	25870	137.6
Solow XLED Broad SMART - 190W	SWX16982	205	30785	150.2
Solow XLED Broad SMART - 65W	SWX16980	68	10585	155.7
Solow XLED Broad SMART- 215W	SWX19038	229	37100	162.0
Solow XLED Narrow - 112W	SWX19045	119	17855	150.0
Solow XLED Narrow - 175W	SWX19046	188	26105	138.9
Solow XLED Narrow - 190W	SWX16996	205	31060	151.5
Solow XLED Narrow - 215W	SWX19047	229	37820	165.2
Solow XLED Narrow - 65W	SWX16994	68	10680	157.1
Solow XLED Narrow SMART - 112W	SWX19039	119	17855	150.0
Solow XLED Narrow SMART - 175W	SWX19040	188	26105	138.9
Solow XLED Narrow SMART - 190W	SWX16986	205	31060	151.5
Solow XLED Narrow SMART - 215W	SWX19041	229	37820	165.2
Solow XLED Narrow SMART - 65W	SWX16984	68	10680	157.1
Solow XLED Opal - 112W	SWX19056	119	15950	134.0
Solow XLED Opal - 175W	SWX19057	188	23315	124.0
Solow XLED Opal - 190W	SWX19058	205	27920	136.2
Solow XLED Opal - 215W	SWX19059	229	33450	146.1
Solow XLED Opal - 65W	SWX19055	68	9540	140.3
Solow XLED Opal - SMART - 175W	SWX19052	188	23315	124.0
Solow XLED Opal - SMART - 190W	SWX19053	205	27920	136.2
Solow XLED Opal - SMART - 215W	SWX19054	229	33450	146.1
Solow XLED Opal - SMART - 65W	SWX19050	68	9540	140.3
Solow XLED Opal - SMART- 112W	SWX19051	119	15950	134.0
Starbeam Area - 123W - SMART - 4000K	SB18343	131	13550	103.4
Starbeam Area - 123W 4000K	SB17556	131	13550	103.4
Starbeam Area - 161W - SMART - 4000K	SB18344	169	17250	102.1
Starbeam Area - 161W 4000K	SB18350	169	17250	102.1
Starbeam Area - 197W - SMART - 4000K	SB19663	203	21200	104.4
Starbeam Area - 197W 4000K	SB19669	203	21200	104.4
Starbeam Area - 31W - SMART - 4000K	SB18340	35	3500	100.0
Starbeam Area - 31W 4000K	SB17553	35	3500	100.0
Starbeam Area - 62W - SMART - 4000K	SB18341	66	6750	102.3
Starbeam Area - 62W 4000K	SB17554	66	6750	102.3
Starbeam Area - 88W - SMART - 4000K	SB18342	95	10150	106.8
Starbeam Area - 88W 4000K	SB17555	95	10150	106.8
Starbeam ECO Area - 31W - 4000K	SB19677	35	4135	118.1
Starbeam ECO Area - 31W - SMART - 4000K	SB19673	35	4135	118.1
Starbeam ECO Area - 48W - 4000K	SB19678	51	6745	132.3
Starbeam ECO Area - 48W - SMART - 4000K	SB19674	51	6745	132.3
Starbeam ECO Roadway - 31W - 4000K	SB19679	35	4225	120.7



Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Starbeam ECO Roadway - 31W - SMART - 4000K	SB19675	35	4225	120.7
Starbeam ECO Roadway - 48W - 4000K	SB19680	51	6890	135.1
Starbeam ECO Roadway - 48W - SMART - 4000K	SB19676	51	6890	135.1
Starbeam Road - 123W - SMART - 4000K	SB18348	131	14250	108.8
Starbeam Road - 123W - SMART - 4000K	SB18360	131	14250	108.8
Starbeam Road - 123W 4000K	SB17564	131	14250	108.8
Starbeam Road - 161W - SMART - 4000K	SB18349	169	18150	107.4
Starbeam Road - 161W 4000K	SB18351	169	18150	107.4
Starbeam Road - 197W - SMART - 4000K	SB19666	203	22300	109.9
Starbeam Road - 197W 4000K	SB19672	203	22300	109.9
Starbeam Road - 31W - SMART - 4000K	SB18345	35	3700	105.7
Starbeam Road - 31W 4000K	SB17561	35	3700	105.7
Starbeam Road - 62W - SMART - 4000K	SB18346	66	7100	107.6
Starbeam Road - 62W 4000K	SB17562	66	7100	107.6
Starbeam Road - 88W - SMART - 4000K	SB18347	95	10700	112.6
Starbeam Road - 88W 4000K	SB17563	95	10700	112.6
Starblaze - 240W - Horizontal Mount	SZ19844	260	28590	110.0
Starblaze - 240W - Vertical Column Mount	SZ19847	260	28590	110.0
Starblaze - 287W - Horizontal Mount	SZ19845	303	33120	109.3
Starblaze - 287W - Vertical Column Mount	SZ19848	303	33120	109.3
Starflood LED - 20W 4000K	STF17569	23	2835	123.3
Starflood LED - 20W 5700K	STF17413	23	2835	123.3
Starflood LED - 20W SMART 4000K	STF17567	23	2835	123.3
Starflood LED - 20W SMART 5700K	STF17410	23	2835	123.3
Starflood LED - 34W 4000K	STF17570	40	4575	114.4
Starflood LED - 34W 5700K	STF17414	40	4575	114.4
Starflood LED - 34W SMART 4000K	STF17568	40	4575	114.4
Starflood LED - 34W SMART 5700K	STF17411	40	4575	114.4
Starflood LED - 42W 4000K	STF17570	47	5400	114.9
Starflood LED - 42W 5700K	STF17415	47	5400	114.9
Starguard LED - 140W - SMART - 4000K	STG19021	150	15850	105.7
Starguard LED - 140W - SMART - 5700K	STG19023	150	15850	105.7
Starguard LED - 140W 4000K	STG17566	150	15850	105.7
Starguard LED - 140W 5700K	STG16355	150	15850	105.7
Starguard LED - 62W - SMART - 4000K	STG19020	68	7045	103.6
Starguard LED - 62W - SMART - 5700K	STG19022	68	7045	103.6
Starguard LED - 62W 4000K	STG17565	68	7045	103.6
Starguard LED - 62W 5700K	STG16354	68	7045	103.6
Swivix 46° Beam - 9W - 3000K	SWV19734	12	1140	95.0
Swivix 46° Beam - 9W - 4000K	SWV19735	12	1230	102.5
Tau LED 1200x600mm - 76W SMART	TU17207	86	8875	103.2
Tau LED 1200x600mm - 76W	TU17211	86	8875	103.2
Tau LED 1200x600mm - 90W	TU17212	106	10350	97.6
Tau LED 1200x600mm - 90W SMART	TU17208	106	10350	97.6
Tau LED 600x600mm - 45W	TU17209	53	5175	97.6
Tau LED 600x600mm - 45W SMART	TU17205	53	5175	97.6
Tau LED 600x600mm - 54W	TU17210	65	6120	94.2
Tau LED 600x600mm - 54W SMART	TU17206	65	6120	94.2
Tego 30° Beam - 14W - 3000K	TEG18032	17	1445	85.0
Tego 30° Beam - 14W - 4000K	TEG18034	17	1555	91.5
Tego 30° Beam - 20W - 3000K	TEG18033	24	1980	82.5
Tego 30° Beam - 20W - 4000K	TEG18035	24	2130	88.8
Tego 38° Beam - 14W - 3000K	TEG18036	17	1430	84.1

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Tego 38° Beam - 14W - 4000K	TEG18038	17	1540	90.6
Tego 38° Beam - 20W - 3000K	TEG18037	24	1960	81.7
Tego 38° Beam - 20W - 4000K	TEG18039	24	2110	87.9
Tego IP65 - 14W - 3000K	TEG18044	17	1270	74.7
Tego IP65 - 14W - 4000K	TEG18046	17	1365	80.3
Tego IP65 - 20W - 3000K	TEG18045	24	1705	71.0
Tego IP65 - 20W - 4000K	TEG18047	24	1835	76.5
Thoroproof ECO LED - 23W	TP19775	31	3700	119.4
Thoroproof ECO LED - 46W	TP19776	53	6625	125.0
Thoroproof LED - 30W	TP19773	37	4820	130.3
Thoroproof LED - 60W	TP19774	72	9470	131.5
Thoroseal LED Type N ( Zones 2 & 22) Broad - 122W	TH16860	135	13600	100.7
Thoroseal LED Type N ( Zones 2 & 22) Broad - 244W	TH16862	270	27100	100.4
Thoroseal LED Type N ( Zones 2 & 22) Narrow - 122W	TH16861	135	13000	96.3
Thoroseal LED Type N ( Zones 2 & 22) Narrow - 244W	TH16863	270	26000	96.3
Tora LED 3000K - 14.9 W/m (4.8m length)	TOR19761	17	935	55.0
Tora LED 3000K - 7.1 W/m (4.8m length)	TOR19760	8	470	58.8
Tora LED 4000K - 13.8 W/m (4.8m length)	TOR19763	15	950	63.3
Tora LED 4000K - 6.6 W/m (4.8m length)	TOR19762	8	470	58.8
Vandalux LED - 34W	VN15758	38	4030	106.1
Vandalux LED - 74W	VN15759	84	8745	104.1
Ventego - 19W	VT17215	22	1635	74.3
Ventego - 56W	VT17216	61	5060	83.0
Viva LED - 16W	VV17589	19	2215	116.6
Viva LED - 16W - ColourControl	VV17250CC	17	1860	109.4
Viva LED - 16W - SMART - ColourActive	VV18811CA	17	1860	109.4
Viva LED - 21W	VV16536	24	3020	125.8
Viva LED - 31W - Colour Control	VV17251CC	34	3700	108.8
Viva LED - 31W - SMART - ColourActive	VV18812CA	34	3700	108.8
Viva LED - 36W	VV16537	41	4775	116.5
Viva LED - 41W - Colour Control	VV19135CC	47	5340	113.6
Viva LED - 41W - SMART - ColourActive	VV19134CA	47	5340	113.6
Viva SMART - 16W	VV17588	19	2215	116.6
Viva SMART - 21W	VV16534	24	3020	125.8
Viva SMART - 36W	VV16869	41	4775	116.5
XL20 - 16W	XL18310	19	2200	115.8
XL20 - 20W	XL18311	23	2725	118.5
XL20 - 29W	XL18312	33	3705	112.3
XL20 - 40W	XL18313	44	4835	109.9
XL20 SMART - 16W	XL18306	19	2200	115.8
XL20 SMART - 20W	XL18307	23	2725	118.5
XL20 SMART - 29W	XL18308	33	3705	112.3
XL20 SMART - 40W	XL18309	44	4835	109.9
XL-Five Daylite LED - 20W	XL17597	23	2735	118.9
XL-Five Daylite LED - 26W	XL16520	30	3425	114.2
XL-Five Daylite LED - 38W	XL16521	43	4625	107.6
XL-Five Daylite LED SMART - 20W	XL17596	23	2735	118.9
XL-Five Daylite LED SMART - 26W	XL16518	30	3425	114.2
XL-Five Daylite LED SMART - 38W	XL16519	43	4625	107.6
XL-Five Prismatic LED - 20W	XL17599	23	3015	131.1
XL-Five Prismatic LED - 26W	XL16524	30	3845	128.2
XL-Five Prismatic LED - 38W	XL16525	43	5280	122.8
XL-Five Prismatic LED SMART - 20W	XL17598	23	3015	131.1

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
XL-Five Prismatic LED SMART - 26W	XL16522	30	3845	128.2
XL-Five Prismatic LED SMART - 38W	XL16523	43	5280	122.8
Zenith-L 17° Beam - 20W - 3000K	ZEN18080	24	2170	90.4
Zenith-L 17° Beam - 20W - 4000K	ZEN18083	24	2335	97.3
Zenith-L 17° Beam - 28W - 3000K	ZEN18081	35	2720	77.7
Zenith-L 17° Beam - 28W - 4000K	ZEN18084	35	2925	83.6
Zenith-L 17° Beam - 35W - 3000K	ZEN18082	41	3370	82.2
Zenith-L 17° Beam - 35W - 4000K	ZEN18085	41	3625	88.4
Zenith-L 28° Beam - 20W - 3000K	ZEN18086	24	1980	82.5
Zenith-L 28° Beam - 20W - 4000K	ZEN18089	24	2130	88.8
Zenith-L 28° Beam - 28W - 3000K	ZEN18087	35	2485	71.0
Zenith-L 28° Beam - 28W - 4000K	ZEN18090	35	2670	76.3
Zenith-L 28° Beam - 35W - 3000K	ZEN18088	41	3075	75.0
Zenith-L 28° Beam - 35W - 4000K	ZEN18091	41	3305	80.6
Zenith-L 41° Beam - 20W - 3000K	ZEN18092	24	1960	81.7
Zenith-L 41° Beam - 20W - 4000K	ZEN18095	24	2110	87.9
Zenith-L 41° Beam - 28W - 3000K	ZEN18093	35	2460	70.3
Zenith-L 41° Beam - 28W - 4000K	ZEN18096	35	2645	75.6
Zenith-L 41° Beam - 35W - 3000K	ZEN18094	41	3045	74.3
Zenith-L 41° Beam - 35W - 4000K	ZEN18097	41	3275	79.9
Zenith-M 30° Beam - 14W - 3000K	ZEN18070	17	1445	85.0
Zenith-M 30° Beam - 14W - 4000K	ZEN18072	17	1555	91.5
Zenith-M 30° Beam - 20W - 3000K	ZEN18071	24	1980	82.5
Zenith-M 30° Beam - 20W - 4000K	ZEN18073	24	2130	88.8
Zenith-M 38° Beam - 14W - 3000K	ZEN18074	17	1430	84.1
Zenith-M 38° Beam - 14W - 4000K	ZEN18076	17	1540	90.6
Zenith-M 38° Beam - 20W - 3000K	ZEN18075	24	1960	81.7
Zenith-M 38° Beam - 20W - 4000K	ZEN18077	24	2110	87.9
Zipline Broad - 22W	ZP16428	24	3825	159.4
Zipline Broad - 22W SMART	ZP16420	24	3825	159.4
Zipline Broad - 33W	ZP16429	36	5845	162.4
Zipline Broad - 33W SMART	ZP16421	36	5845	162.4
Zipline Broad - 41W	ZP16430	44	6955	158.1
Zipline Broad - 41W SMART	ZP16422	44	6955	158.1
Zipline Broad - 53W	ZP16431	57	8825	154.8
Zipline Broad - 53W SMART	ZP16423	57	8825	154.8
Zipline Broad - 64W	ZP16601	67	10025	149.6
Zipline Broad - 64W SMART	ZP16600	67	10025	149.6
Zipline Double Asymetric - 22W	ZP16565	24	3935	164.0
Zipline Double Asymetric - 22W SMART	ZP16561	24	3935	164.0
Zipline Double Asymetric - 33W	ZP16566	36	6020	167.2
Zipline Double Asymetric - 33W SMART	ZP16562	36	6020	167.2
Zipline Double Asymetric - 41W	ZP16567	44	7160	162.7
Zipline Double Asymetric - 41W SMART	ZP16563	44	7160	162.7
Zipline Double Asymetric - 53W	ZP16568	57	9090	159.5
Zipline Double Asymetric - 53W SMART	ZP16564	57	9090	159.5
Zipline Double Asymetric - 64W	ZP16605	67	10325	154.1
Zipline Double Asymetric - 64W SMART	ZP16605	67	10325	154.1
Zipline Narrow - 22W	ZP16424	24	3900	162.5
Zipline Narrow - 22W SMART	ZP16416	24	3900	162.5
Zipline Narrow - 33W	ZP16425	36	5960	165.6
Zipline Narrow - 33W SMART	ZP16417	36	5960	165.6
Zipline Narrow - 41W	ZP16426	44	7090	161.1

Luminaire	Cat. No.	Circuit Watts	Luminaire Lumens	LL/CW
Zipline Narrow - 41W SMART	ZP16418	44	7090	161.1
Zipline Narrow - 53W	ZP16427	57	8995	157.8
Zipline Narrow - 53W SMART	ZP16419	57	8995	157.8
Zipline Narrow - 64W	ZP16603	67	10215	152.5
Zipline Narrow - 64W SMART -	ZP16602	67	10215	152.5